STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leskage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator	·!	JNIO	N OIL	COM	PANY	OF CA	LIFOR	NIA I	.case _	RI	NCON_U	NIT	Wo		
Location of Well:	Unit .	D	_ Sec	12	_Twp.		UNOCA 26N		lge	7W		Cou	nty	RIO ARRIBA	
NAME OF RESERVOIR OR POOL						TYPE OF PROD. (Oll or Gae)			METHOD OF PROD. (Flow or Art. Lift)		PROD, MEDIUM (Tog. or Cag.)				
Upper Completion BLANCO MESA VE			A VE	RDE		GAS			FLOW			TUBING			
Lower Completion BASIN DAKOTA							GAS		FLOW		TUBING				
						PR	E-FLOV	7 SHU	T-IN P	RESSURE	DATA				
Upper Completion MAY 05 1996 10:00AM Lewer Completion MAY 05 , 1996 10:00AM					3 Ime shut-in	DAYS BI press. paig			TRG.	380	180 V NO Stabilized? (Yea or No)				
Consessed	-1 C	detel	· ΜΛ	v ng	. 199	26 10):20AM	FLOW	TEST		dueing (Lipp	er or Lowerk	LOWER		
Commenced at (hour, TIME (hour, date)			LAPSED TIME			PRESSU				PROD.	D. ZONE EMP.		REMARKS		
			24 HR		IR	430 440	1	TBG 98		76	76°		Q = 302 MCF/D		
05/10/96			48 HRS			CSG. 430 TBG. 410		TBG.	87	69°		Q = 246 MCF/D		6 MCF/D	
		_ -			-				· · · · · · · · · · · · · · · · · · ·					· · · · · · · · · · · · · · · · · · ·	
•					-								·		
	-:- -							<u> </u>				•	<u>.</u>		
Productio	on rate	duri	ing test		<u>.l.,</u>				•	.d			•	•	
Oil:			1	_ BOI	PD bas	ed on _		1	Bbls. in	1	_ Hours.	0	Grav	GOR	
G25:						1	MCFPD	; Teste	ւժ փոս	(Orifice	or Meter)):			
						MI	D-TEST	SHUT	r-in pi	RESSURE	DATA				
Upper	Hour, da	te shut	-In			Length of time shut-in				SI press. psig			Stabilized?	(Yes or No)	
Lower Completion						Length of time shut in				SI press. paig Sta			İ	(Yes or No)	

FLOW TEST NO. 2

	late) * *	,	Zone producing (Upper or Lower):				
TIME	LAPSED TIME	PRES	SURE	PROD. ZONE			
(hour, date)	SINCE **	Upper Completion	Lower Completion	TEMP,	REMARKS		
					<u></u>		
							
		*****		-			
	İ						
	-	243 278 (141) (111) (111)					
oduction rate d	-) based on	Rhie in		Grav GOR		
		Discu on	DDIS. III .	Hours.	Grav GOR		
as:		MCFF	D: Tested thm (Orifice or Meter)	:		
				Office of inetery	•		
marks:							
					· · · · · · · · · · · · · · · · · · ·		
nereby certify th	nat the informatio	n herein containe	d is true and com	plete to the best	of my knowledge.		
	hat the informatio						
			. 19 Op	erator UNION	OIL COMPANY OF CALIFORNIA DB		
	chnny Rollins I Conservation Di	vision	. 19 Op	erator UNION	OIL COMPANY OF CALIFORNIA DB		
		vision	. 19 Op	erator UNION	OIL COMPANY OF CALIFORNIA DB		
oproved <u>J</u> New Mexico O	Conservation Di MAY 17199	vision 6	. 19 O _F	R.L.	OIL COMPANY OF CALIFORNIA DB UNOC Caine		
oproved <u>J</u> New Mexico O	chnny Rollins I Conservation Di	vision 6	. 19 O _F	R.L.	OIL COMPANY OF CALIFORNIA DB		

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been distrubed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- Flow Test 'No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

that the previously produced 200e shall remain shur-in while the 200e which was previously shur-in is produced.

7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).