

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 4674-0135
Expires: March 31, 1993

COPY

RECEIVED
BLM

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT-" for such proposals.

SUBMIT IN TRIPLICATE

1. TYPE OF WELL

OIL WELL ☐ GAS WELL ☒ OTHER ☐

2. NAME OF OPERATOR

CONOCO INC.

3. ADDRESS AND TELEPHONE NO.

10 Desta Drive, Ste. 100W Midland, Texas 79705-4500 (915-686-5424)

4. LOCATION OF WELL (Footage, Sec., T., R., M., or Survey Description)

1190' FNL & 1845' FWL, UNIT LETTER "C", SEC 16, T-26-N, R-04-W

5. LEASE DESIGNATION AND SERIAL NO.

CONT. 104

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

JICARILLA

7. IF UNIT OR CA, AGREEMENT DESIGNATION

JICARILLA E

8. WELL NAME AND NO.

15E

9. API WELL NO.

30-039-25736

10. FIELD AND POOL, OR EXPLORATORY AREA

BLANCO MV/BASIN DAKOTA

11. COUNTY OR PARISH, STATE

RIO ARRIBA, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other: Spud & casing report - 4-1/2"
☐ Change of Plans
☒ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log Form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

03/01/98 Stage 1: Ran 179 joint 4-1/2", 11.6#, LTC, K-55 casing. Depth of shoe 7921', depth of collar 7876'. Cement with 80sx of 35/65 POZ, 8% Gel, 6.25#/sk Gilsonite, .25#/sk Cello Flake, 2% CaCl2. Followed by 100 sks. Class H, 0.7% BA-56, 0.3% CD-32, .25#/sk Cello Flake. Displaced with 122 bbls of mud. Muddy and full returns with no cement returns. Floats held. Bumped plug @ 10:00 a.m. on 03/01/98 w/ 750 psi.

03/02/98 Stage2: Stage collar depth 6125' and 3733', manufacturer of stage tool Gemco. Cement with 175 sx of 50/50 POZ, 4% Gel, 0.3% FL-52, 0.3% CD-32, 6.25#/sk Gilsonite, 2% KCl. Displaced 95 bbls of mud with no returns, floats held. Bumped plug @ 1:35 p.m. on 03/01/98 with 700 psi.

RECEIVED
MAY 28 1998
OIL CON. DIV.
DIST. 3

14. I hereby certify that the foregoing is true and correct

SIGNED

Sylvia Johnson

TITLE SYLVIA JOHNSON, As Agent for Conoco Inc. DATE 03/05/98

(This space for Federal or State office use)

APPROVED BY

David R. Sitzler

TITLE

Lands and Mineral Resources

DATE

MAY 11 1998

Conditions of approval, if any:

CoA. ~~submit~~ submit sundry identifying top of cement

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.