Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED

Budget Bureau No. 1004-0135

Expires: March 31, 1993

LEASE DESIGNATION AND SERIAL NO. **CONT 106** SUNDRY NOTICES AND REPORTS ON WELLS IF INDIAN, ALLOTTEE OR TRIBE NAME Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. **JICARILLA** Use "APPLICATION FOR PERMIT-" for such proposats 7. IF UNIT OR CA, AGREEMENT DESIGNATION SUBMIT IN TRIPLICATE JICARILLA B TYPE OF WELL 8. WELL NAME AND NO. OIL WELL **GAS WELL** OTHER #13M 2. NAME OF OPERATOR 9. API WELL NO. CONOCO INC 30-039-25773 ADDRESS AND TELEPHONE NO. 10. FIELD AND POOL, OR EXPLORATORY AREA P.O. Box 2197, DU 3066, Houston, TX 77252-2197 (281) 293-1613 **BLANCO MESA** VERDE/BASIN DAKOTA LOCATION OF WELL (Footage, Sec., T., R., M., or Survey Description) 11. COUNTY OR PARISH, STATE 1060' FNL & 1040 FWL, Section 36, T26N, R04W, UNIT LETTER "D" RIO ARRIBA COUNTY CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12. TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Abandonment Change of Plans Recompletion **New Construction** Subsequent Report Plugging Back Non-Routine Fracturing Final Abandonment Notice Casing Repair Water Shut-Off Altering Casing Conversion to Injection Other: Casing Report Dispose Water (Note: Report results of multiple completion on Well Completion or Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) 7/8/00 Well spudded at 1:30 p.m. Drilled surface hole. Ran 11 joints, 9-5/8" set at 508', Hole size 12-1/4", 36#, J-55, ST&C casing. Cement with 300 sxs Class B 7/9/00 + 0.25% D-29 + 2% BWOC S-001 + 0.1% BWOC D-46 at 15.6 PPG. Displaced with 36.5 bbls fresh water. Floats not held. Bumped plug at 10:24 p.m. with 522 psi. Ran 192 joints, 7" set at 8135', Hole size 8-3/4", 23#/26#, M-95, ST&C casing. 8/9/00 Stage 1: Cement with 252 sxs of Litecrete cement + 0.25 D-29 + 5.18 D-154 + 42.97 D-124 + 0.5% BWOC D-112 + 51.85 D-049 + 0.11 D-065 + 0.03 GPS D-047 at 9.5 PPG. Displaced with 120 bbls fresh water and 194.5 bbls mud. Floats held. Bumped plug at 8:30 p.m. with 940 psi. Stage 2: Cement with 282 sxs of 50/50 Poz + 30 D-048 + 0.2% BWOC D-167 + 0.25 D-29 k+ 47 D-907 + 2.75% BWOC D-020 + 0.2% BWOC D-046 at 12.4 PPG. Displaced with 70 bbls fresh water and 131 bbls mud. Floats held. Bumped plug at 2;10 a.m. with 1290 psi. Stage 3: Cement with 271 sxs of Class B + 0.2% BWOC D-046 + 3% BWOC D-079 + 94 D-907 + 2% BWOC SQQ1 + 0.25 D-029 at 11.4 PPG. Displaced with 135 bbls fresh water. Floats held. Bumped plug at 8:26 a.m. with 1795 psi. 14. I hereby certify that the foregoing is true and correct SIGNED TITLE DEBRA SITTNER, As Agent for Conoco Inc. DATE 8/25/00 State office use) (This space for Federal or Land, and Morral E. Journe 7 2000 SEP APPROVED BY Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the Unites States any false,