

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 03553

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Breesh "D"

9. WELL NO.

341 (PD)

10. FIELD AND POOL, OR WILDCAT

**So. Blanco PC
Basin Dakota**

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Section 21-26N-6W

12. COUNTY OR PARISH 13. STATE

Bio Arriba

New Mexico

1.

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Caulkins Oil Company

3. ADDRESS OF OPERATOR

Box 780, Farmington, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1190' FHL and 1650' FEL of Section 21-26N-6W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6652 GL 6665 KB

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☒

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)


17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled to 7500'. Cemented 4 1/2" casing at 7494' as follows:

**0 to 94.15 5 1/8" OD 15.5# J-55 LT&C
94.15 to 887.44 4 1/2" OD 11.6# J-55 ST&C
887.44 to 6461.00 4 1/2" OD 10.5# J-55 ST&C
6461.00 to 7494.00 4 1/2" OD 11.6# J-55 ST&C**

**Cemented through shoe with 260 sacks Class A cement containing 12% gel and 12% gilsonite per sack followed by 100 sacks latex cement. Plug down 1:30 AM 8-12-65
Cemented through Halliburton DV Multistage Cementing Collar with 950 sacks Class C cement containing 4% gel and 12% gilsonite per sack. Closed DV collar with 2700# pressure. Plug down at 6:00 AM 8-12-65**

Cement will be allowed to set at least 72 hours before completion operations are started



18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Superintendent

DATE

8-12-65

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE : 1963 - O-685229

897-851

