



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. NE 033-A
Unit Bayless-Cynthia

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

December 3, 1962

Well No. 1 is located 660 ft. from IX line and 660 ft. from IV line of sec. 19
NE 1/4 Sec. 19 (1/4 Sec. and Sec. No.) 26N (Twp.) 1E (Range) 100W (Meridian)
W C (Field) Rio Arriba (County or Subdivision) New Mexico (State or Territory)

The elevation of the derrick floor above sea level is 7347 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Drilled 8-3/4" hole to 3300 feet. Ran Electric log. Cement 7" casing @ 3275 feet with 100 sacks. Drilled 6-1/4" hole with air to 4850 feet. Cemented 4-1/2" casing @ 4288 feet with 100 sacks. Plugged back open hole with sand to 4600 feet. Frac treated open hole with 1000 barrels lease crude. Flowed back 700 bbls. load oil. Ran 2" tubing to 4580 feet, perforations @ 4530 feet. Ran rods and installed pump.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Mountain States Petroleum Corporation
Address P. O. Box 1741
Farmington,
New Mexico
By Jack A. Cole
Title Geologist