## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Wil	A2552	
NM	03553	

5. LEASE

permitting of the interior	
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different	7. UNIT AGREEMENT NAME
reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas	Breech D
well well well other	9. WELL NO.
2. NAME OF OPERATOR	140
Caulkins Oil Company	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Blanco Mesa Verde Basin Dakota
P.O. Box 780 Farmington, New Mexico	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA
below.) AT SURFACE: 990' From North & 990' From East	Section 11 26 North 6 West 12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: Same	1 · 1
AT TOTAL DEPTH: Same	Rio Arriba New Mexico 14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE.	ATT NO.
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
- parameter - para	6600 KB
REQUEST FOR APPROVAL TO:  SUBSEQUENT REPORT OF THE TOTAL	
	400
FRACTURE TREAT  SHOOT OR ACIDIZE  SHOOT OR ACIDIZE	
SHOOT OR ACIDIZE	(NOTE: Report results of multiple completion or zone
PULL OR ALTER CASING 🔲	
MULTIPLE COMPLETE  CHANGE ZONES  MULTIPLE COMPLETE  CHANGE ZONES  MULTIPLE CASING  ULS. CADLOCIO IN FATRICING IN THE PROPERTY OF THE PROPERTY	SUN ER STEEL
ABANDON*	
(other) Filing extension NTL 2B	그 그는 그 이 이 원진불량 이 혹시작성 했다.
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertinent.	e all pertinent details, and give pertinent dates, irectionally drilled, give subsurface locations and
measured and true vertical depths for all markers and zones pertinen	nt to this work.)*
We hereby request 90 days antique of 6:1:	
We hereby request 90 day extension of filin for water disposal pit as required NTL 2B.	g deadline of application
for water disposal pit as required NTL 28.	
Well should be connected to pipeline by Jan	1 1002
more should be connected to pipeline by Jan	. 1, 1963.
	10,00
	10000
	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \
Subsurface Safety Valve: Manu. and Type	
	Ft.

the F

\*See Instructions on Reverse Side