16.

UNITED STATES DEPARTMENT OF THE INTERIOR Verse alde)

SUBMIT IN TRIPLICATES Other instructions on

Form approved, Budget Bureau No. 5. LEASE BESIGNATION AND BERIAL NO.

G. IF INDIAN, ALLOTTLE OR TRIBE NAME

GEOLOGICAL SURVEY

c	VOOLALL	NICTICES	AND	REPORTS	ONL	WELLC
5	UNDRY	NOTICES	AND	REPORTS	ON	WELLS

(Po not use this form	Y NOTICES AND REPORTS ON for proposals to drill or to deepen or plug back "APPLICATION FOR PERMIT—" for such proposals	to a different reservoir.		
OIL X GAS WELL X	OTHER		7. UNIT AGREEMENT NA	
NAME OF OPERATOR Skelly Oil Comp			East Bisti 8. FARM OR LEASE NAM	
. ADDRESS OF OPERATOR	reet, Denver, Colorado 80203	/ Million	9. WELL NO. 73	
LOCATION OF WELL (Report See also space 17 below.) At surface	location clearly and in accordance with any State	OIL CON SU	Bisti Lowe	
5301	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA			
			Section 35	
4. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT,		12. COUNTY OR PARISH	13. STATE
	6749' GR 6761' k	KΒ	San Juan	New Mexic

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:				SUBSEQUENT REPORT OF:		
TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL (Other)		PULL OR ALTER CASING MULTIPLE COMPLETE ABANDON* CHANGE PLANS	X	WATER SHUT-OFF FRACTURE TREATMENT SHOOTING OR ACIDIZING (Other) (Note: Report results of mp Completion or Recompletion is	REPAIRING WELL ALTERING CASING ABANDONMENT* Itiple completion on Well keport and Log form.)	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

This well has reached the economic limit and is no longer profitable to operate. Plans are to plug and abandon this well; plugging as follows:

First Plug - 100' plug across Gallup Zone perforations 5353-5404'

Second Plug - 50' inside the 5-1/2" casing and 50' above where casing is shot in two Third Plug - 150' cement plug extending downward from above the Fruitland Coal section across the Pictured Cliffs Sand

Fourth Plug - 100' plug at bottom of Ojo Alamo Sand (unless surface casing is set through the Ojo Alamo Sand)

10 sacks of cement in top of surface casing with dry hole marker

18. I hereby certify that the foregoing is true and correct	TITLE District Opera	tions Supt. DA	June 10, 1971
(This space for Federal or State office us			
APPROVED BY CONDITIONS OF APPROVAL, IF ANY:	TITLE	DA	TE