
GPO 9 18 50 7



(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

Land Office	Sar	ite.	Po
Lease No	8.	97	958
[]m!e	L	£.	Lookhart

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO CHANGE PLANS. NOTICE OF INTENTION TO TEST WATER SUITOFF. NOTICE OF INTENTION TO TEST WATER SUITOFF. NOTICE OF INTENTION TO SHOULD OR REPAIR WELL. NOTICE OF INTENTION TO SHOULD OR REPAIR WELL. NOTICE OF INTENTION TO SHOULD OR REPAIR WELL. NOTICE OF INTENTION TO PULL OR ALTER CASING. NOTICE OF INTENTION TO SHOULD REPAIR. NOT	NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	inotion I
NOTICE OF INTENTION TO TEST WATER SHUT-OFF. NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL SUBSCOURT REPORT OF ALTERING CASING. NOTICE OF INTENTION TO SHOOT OR ACIDIZE. NOTICE OF INTENTION TO SHOOT OR ACIDICE. NOTICE OF INTENTION TO SH			
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL NOTICE OF INTENTION TO SHOOT OR ACIDIZE NOTICE OF INTENTION TO SHOOT OR ACIDIZE NOTICE OF INTENTION TO SHOOT OR ACIDIZE NOTICE OF INTENTION TO PULL OR ALTER CASING NOTICE OF INTENTION TO ABANDON WELL Report of sand-fracing (INDICATE ABOVE BY CHECK MARK NATURE OF PEPORT, NOTICE, OR OTHER DATA) NOTICE OF INTENTION TO SHOOT WELL Report of sand-fracing (INDICATE ABOVE BY CHECK MARK NATURE OF PEPORT, NOTICE, OR OTHER DATA) NOTICE OF INTENTION TO SHOOT WELL Report of sand-fracing (INDICATE ABOVE BY CHECK MARK NATURE OF PEPORT, NOTICE, OR OTHER DATA) NOTICE OF INTENTION TO SHOOT WELL Report of sand-fracing (INDICATE ABOVE BY CHECK MARK NATURE OF PEPORT, NOTICE, OR OTHER DATA) NOTICE OF INTENTION TO SHOOT WELL Report of sand-fracing (INDICATE ABOVE BY CHECK MARK NATURE OF PEPORT, NOTICE, OR OTHER DATA) NOTICE OF INTENTION TO SHOOT WELL Report of sand-fracing (INDICATE ABOVE BY CHECK MARK NATURE OF PEPORT, NOTICE, OR OTHER DATA) NOTICE OF INTENTION TO SHOOT WELL Report of sand-fracing (INDICATE ABOVE BY CHECK MARK NATURE OF PEPORT, NOTICE, OR OTHER DATA (INDICATE ABOVE BY CHECK MARK NATURE OF PEPORT, NOTICE, OR OTHER DATA (INDICATE ABOVE BY CHECK MARK NATURE OF PEPORT, NOTICE, OR OTHER DATA (INDICATE ABOVE BY CHECK MARK NATURE OF PEPORT, NOTICE, OR OTHER DATA (INDICATE ABOVE BY CHECK MARK NATURE OF PEPORT, NOTICE, OR OTHER DATA (INDICATE ABOVE BY CHECK MARK NATURE OF PEPORT, NOTICE, OR OTHER DATA (INDICATE ABOVE BY CHECK MARK NATURE OF PEPORT, NOTICE, OR OTHER DATA (INDICATE ABOVE BY CHECK MARK NATURE OF PEPORT, NOTICE, OR OTHER DATA (INDICATE ABOVE BY CHECK MARK NATURE OF PEPORT, NOTICE, OR OTHER DATA (INDICATE ABOVE BY CHECK MARK NATURE OF PEPORT, NOTICE, OR OTHER DATA (INDICATE ABOVE BY CHECK MARK NATURE OF PEPORT, NOTICE, OR OTHER DATA (INDICATE BY CHECK MARK NATURE OF PEPORT, NOTICE BY CHECK MARK NATURE OF PEROPE.			
NOTICE OF INTENTION TO SHOOT OR ACIDIZE NOTICE OF INTENTION TO PULL OR ALTER CASING NOTICE OF INTENTION TO PULL OR ALSO CASING NOTICE OF INTE			·
NOTICE OF INTENTION TO PULL OR ALTER CASING. NOTICE OF INTENTION TO ABANDON WELL Report of partorstance (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DAT	1		i
NOTICE OF INTENTION TO ABANDON WELL Report of send-freeding (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) NOTEMBER 1, 19 I. E. Lockhart Well No. 3. Is located 1980 ft. from III line and 1989 ft. from III line of sec. 33 SM/4-HE/A Section 33 251 102 (Moridian) Report of send-freeding Notember 1, 19 I. E. Lockhart Well No. 3. Is located 1980 ft. from III line and 1989 ft. from III line of sec. 33 SM/4-HE/A Section 33 251 102 (Moridian) Report of sending Section 33 102 (Moridian) Notember 1, 19 III line and 1989 ft. from III line of sec. 33 SM/4-HE/A Section 33 251 (Moridian) Report of sending Section 34 102 (Moridian) Notember 1, 19 III line of sec. 33 SM/4-HE/A Section 33 251 (Moridian) Report of sending Section 33 251 (Moridian) Report of sending Section 34 102 (Moridian) R			1
(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) Report of sand-freeing November 1, 19			X
(Peid) The elevation of the derrick floor above sea level is DETAILS OF WORK State names of and expected depths to objective sands; show size, weights, and lengths of proposed casings indicate analysis, and all other important proposed work) The saling perforations 5362-5374, a 5396-5412, with 4 welex jet shots per ft., total Saling perforations 5362-5374, a 5396-5412, with 40,000, sand a 32,256 graph 19506, Max. pressure 21006, Nine, pressure 1800%, average inj. rate 45.2 Bit treatment 22 min. Shut down pressure 850%, pressure dropped to zero in 4 his lunderstand that this plan of work must receive approval in writing by the Geological Surey before operations may be money. Box 426 Address Parmington; New Mexico	NOTICE OF INTENTION TO ABANDON WELL	· II	X
Vell No. 3. is located 1980 ft. from line and 1980 ft. from E line of sec. 32 SN/L-NR/A Section 33 25% (Genge) (Moridian) Residual Sec. No.) (Twp.) (Range) (Moridian) Residual Sec. No.) (Twp.) (Range) (Moridian) Sam Juan (County or Subdivision) (State or Terripary) The elevation of the derrick floor above sea level is ft. DETAILS OF WORK State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate randeling joints, and all other important proposed work) Junts. 52" casing set at 5526' executed with 125 sacks posmix & 125 sacks region of the same states of the same state	(INDICATE ABOVE BY CHECK MAR		
Vell No. 3. is located 1980 ft. from line and 1980 ft. from E line of sec. 32 SN/L-NR/A Section 33 25% (Genge) (Moridian) Residual Sec. No.) (Twp.) (Range) (Moridian) Residual Sec. No.) (Twp.) (Range) (Moridian) Sam Juan (County or Subdivision) (State or Terripary) The elevation of the derrick floor above sea level is ft. DETAILS OF WORK State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate randeling joints, and all other important proposed work) Junts. 52" casing set at 5526' executed with 125 sacks posmix & 125 sacks region of the same states of the same state		Neron	have 1 10
DETAILS OF WORK State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate randding lobs, casing set at 5526' casented with 125 sacks possis & 125 sacks registed 52' casing set at 5526' casented with 125 sacks possis & 125 sacks registed 52' casing 5362-5374' & 5396-5412' with 4 welex jet shots per ft., total casing perforations 5362-5374' & 5396-5412' with 40,000% sand & 32,256 gaps 1950%, Max. pressure 2100%, Min. pressure 1800%, average inj. rate 45.2 Bit treatment 22 min. Shut down pressure 850%, pressure dropped to zero in 4 his lunderstand that this plan of work must receive approval in writing by the Geological Survey before operations man formation. Lunderstand that this plan of work must receive approval in writing by the Geological Survey before operations man formation. Box 426 Address — Farmington; New Mexico	Block Sec. and Sec. No.) (Twp.)	Juan New Mexi	eo PCEN
DETAILS OF WORK State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate randding lobs, casing set at 5526' casented with 125 sacks possis & 125 sacks registed 52' casing set at 5526' casented with 125 sacks possis & 125 sacks registed 52' casing 5362-5374' & 5396-5412' with 4 welex jet shots per ft., total casing perforations 5362-5374' & 5396-5412' with 40,000% sand & 32,256 gaps 1950%, Max. pressure 2100%, Min. pressure 1800%, average inj. rate 45.2 Bit treatment 22 min. Shut down pressure 850%, pressure dropped to zero in 4 his lunderstand that this plan of work must receive approval in writing by the Geological Survey before operations man formation. Lunderstand that this plan of work must receive approval in writing by the Geological Survey before operations man formation. Box 426 Address — Farmington; New Mexico	The elevation of the derrick floor above sea le	evel isft.	M 19
State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate randding jobs, casing 53 casing set at 5526' camented with 125 sacks posmix & 125 sacks region of 52 casing 5362-5374' & 5396-5412' with 4 welex jet shots per ft., total it. 52" casing perforations 5362-5374' & 5396-5412' with 40,000% sand & 32,256 graph 1950%, Max. pressure 2100%, Min. pressure 1800%, average inj. rate 45.2 Bit treatment 22 min. Shut down pressure 850%, pressure dropped to zero in 4 his limited of the first of		الو	Mu a
State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mandding lobs, and all other important proposed work) July 52 casing set at 5526 comented with 125 sacks possing a 125 sacks region of 52 casing 5362-5374 a 5396-5412 with 4 wellow jet shots per ft., total action of the same same same same same same same sam	Tron i		
July 52" casing set at 5526' comented with 125 sacks possix & 125 sacks registed 52" casing 5362-5374' & 5396-5412' with 4 Welex jet shots per ft., total 52" casing perforations 5362-5374' & 5396-5412' with 40,000% sand & 32,256 gs pr 1950%, Max. pressure 2100%, Min. pressure 1800%, average inj. rate 45.2 Bit treatment 22 min. Shut down pressure 850%, pressure dropped to zero in 4 his land that this plan of work must receive approval in writing by the Geological Sustey before operations may be a manual company. SKELLY OIL COMPANY Box 426 Address — Farmington, New Mexico By		. 4 3 . x 2 x 3 .	TEAT A SECTION TO
I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be a survey of the Geological Survey before operations may be a survey of the Geological Survey before operations may be a survey of the Geological Survey before operations may be a survey of the Geological Survey before operations may be a survey of the Geological Survey before operations may be a survey of the Geological Survey before operations may be a survey of the Geological Survey before operations may be a survey of the Geological Survey before operations may be a survey of the Geological Survey before operations may be a survey of the Geological Survey before operations may be a survey of the Geological Survey before operations may be survey of the Geological Survey before operations may be survey of the Geological Survey before operations may be survey of the Geological Survey before operations may be survey of the Geological Survey before operations may be survey of the Geological Survey before operations may be survey of the Geological Survey before operations may be survey of the Geological Survey before operations may be survey of the Geological Survey before operations may be survey of the Geological Survey before operations may be survey of the Geological Survey before operations may be survey of the Geological Survey before operations may be survey of the Geological Survey before operations may be survey of the Geological Survey before operations and the survey of the Geological Survey before operations and the survey of the Geological Survey before operations and the survey of the Geological Survey before operations and the survey of the Geological Survey before operations are survey of the Geological Survey before operations and the survey of the Geological Survey before operations and the survey of the Geological Survey before operations are survey of the Geological Survey before operations are survey of the Geological Survey before operations are survey of the Geological Surve		. 4 3 . x 2 x 3 .	udding jobs. con
Company SKELLY OIL COMPANY Box 426 Address Farmington, New Mexico By	(State names of and expected depths to objective sands; show s ing points, and all ints. 5 chaing set at 5526 cemon	sizes, weights, and lengths of proposed casings; indicate in lother important proposed work)	secks reg
	(State names of and expected depths to objective sands; show a ing points, and all Juts. 52 casing set at 5526 cemented 52 casing 5362-5374 a 5396-541 to. 52 casing perforations 5362-5374 a 5396-541 to.	sizes, weights, and lengths of proposed casings; indicate me lother important proposed work) ated with 125 sacks possix & 125 12' with 4 welex jet shots per ft 25396-5412' with 40,000 sand & pressure 1800% average inj. rat	sacks reg. ., total 32,256 ga te 45.2 BP
Title District Superintendent	(State names of and expected depths to objective sands; show a ing points, and all Juts. 52" casing set at 5526' cemented 52" casing 5362-5374' a 5396-541 to. 52" casing perforations 5362-5374' a 5396-541 to. 1 understand that this plan of work must receive approval Company SKELLY OIL COMPANY Box 426	izes, weights, and lengths of proposed casings; indicate in lother important proposed work) Ated with 125 sacks possin & 125 12' with 4 welex jet shots per ft 15396-5412' with 40,000 sand & pressure 1800%, average inj. rate are 850%, pressure dropped to ser	sacks reg. ., total 32,256 ga te 45.2 BP