Form approved, Bud of Bureau No. 42 R1421. SUBMIT IN TRIPLICATES UNITED STATES DEPARTMENT OF THE INTERIOR (Other in instructions 5. LEASE DIFFE SATION AND BEREAU NO. GEOLOGICAL SURVEY SF 079958 6. IF INDIAN, ALLOTTEE OR THIRE NAME SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals.) 7. UNIT AGREEMENT NAME WELL X OTHER WELL East Bisti Unit 2. NAME OF OPERATOR , FARM OR LEASE NAME Skelly Oil Company 3. ADDRESS OF OPERATOR 9. WELL NO. 1860 Lincoln Street, Denver, Colorado 80203 63 LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 10. FIELD AND POOL, OR WILDCAT Bisti Lower Gallup 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 1980' FNL & 1980' FEL Section 33-25N-10W Section 33-25N-10W 12. COUNTY OR PARISH | 13. STATE 14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, OR, etc.) 6823' GR 6832' DF San Juan New Mexico 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: REPAIRING WELL PULL OR ALTER CASING WATER SHUT-OFF TEST WATER SHUT-OFF FRACTURE TREAT MULTIPLE COMPLETE FRACTURE TREATMENT ALTERING CASING X ABANDON* SHOOTING OR ACIDIZING ABANDON MENT® SHOOT OR ACIDIZE REPAIR WELL CHANGE PLANS (Note: Report results of multiple completion on Weil Completion or Recompletion Report and Log form.) (Other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) • This well has reached the economic limit and is no longer profitable to operate. Plans are to plug and abandon this well; plugging as follows: First Plug - 100' plug across Gallup Zone perforations 5362-5412' Second Plug - 50' inside the 5-1/2" casing and 50' above where casing is shot in two Third Plug - 150' cement plug extending downward from above the Fruitland Coal section across the Pictured Cliffs Sand Fourth Plug - 100' plug at bottom of Ojo Alamo Sand (unless surface casing is set through the Ojo Alamo Sand) 10 sacks of cement in top of surface casing with dry hole marker