



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. 078302
Unit Robert L. Hairston

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	X
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Farmington, New Mexico, October 6, 1955

Well No. 1 is located 990 ft. from N line and 990 ft. from E line of sec. 31

NE/4 Section 31
(1/4 Sec. and Sec. No.)

T-25-N
(Twp.)

R-9-W
(Range)

MMN
(Meridian)

Wildcat
(Field)

San Juan
(County or Subdivision)

New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is 6799 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Notice of Intention to Abandon Well, Form 9-331a, was approved August 26, 1955. Well was drilled to a total depth of 6650 and plugged back to 2630 as previously reported. Well was permanently plugged and abandoned as follows: 10 3/4" casing set at 203 feet with 150 sacks cement and left in hole. 7 5/8" intermediate casing was set at 4525 feet with 110 sacks cement with 8% gel, 100 cubic feet Stratocrete and 50 sacks neat cement. 2283 feet of 7 5/8" casing was recovered. 5 1/2" production casing was set at 6403 feet with 50 sacks cement. 5973 feet of 5 1/2" casing recovered. On August 27, 1955 plugged hole as follows: Filled hole with heavy mud to 2000 feet, 2000 - 1800 feet with 96 sacks cement, 1250 - 1100 feet with 72 sacks cement, spotted 50 sacks cement plug at 200 feet and 25 sacks cement plug at surface in top of 10 3/4" casing. Hole was filled with heavy mud below and between intervals of solid cement plugs. A 4-foot pipe marker was erected and ground level restored to original contours, as per regulations.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company STANWILL OIL & GAS CO.

Address FARMINGTON, N.M.

By L.O. Spencer
Title Field Supt.

THE HISTORY OF THE UNITED STATES OF AMERICA

BY
JOHN F. JOHNSON
OF THE
NEW YORK PUBLIC LIBRARY
ASTOR LENOX TILDEN FOUNDATION
1897



THE HISTORY OF THE UNITED STATES OF AMERICA
BY
JOHN F. JOHNSON
OF THE
NEW YORK PUBLIC LIBRARY
ASTOR LENOX TILDEN FOUNDATION
1897

1897