

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE
(Other Institutions or to
reverse side)

Form approved
Budget Control No. 42 R1121

5. LEASE DESIGNATION AND SERIAL NO.

SF 079958

6. IF INDIAN, ALAOTIE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for application to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such purposes.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2.

NAME OF OPERATOR
Skelly Oil Company

3.

ADDRESS OF OPERATOR
1860 Lincoln Street - Denver, Colorado 80203

4.

LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

660' FNL and 660' FEL Section 33-25N-10W

14.

PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6851' DF

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETION

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other)

(NOTE: Report results of multiple completion on Well
Completion or Rec completion Report and Log form.)

17.

DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

All depths shown are from Ground Level.

7/24/71 - MI&RU Aztec Well Service Unit. Pulled rods.

Spotted cement plug from 5382' to 5282'. Pulled 2" tubing.

Worked 5 1/2" casing to free same. Rigged up Blue Jet, perforated from 1724' to 1725' w/4 shots. Ran 2" tubing, Spotted cement plug from 1725' to 1575'. Pulled tubing. Shot casing off at 1308'. Spotted cement plug from 1358' to 1258', 50' inside casing stub and 50' above casing stub. Pulled up the hole.

Spotted cement plug from 985' to 885'. Pulled 42 joints 1315' of 5 1/2" casing.

Spotted 10' cement plug in surface casing. Installed dry hole marker.

Completed P&A 8/6/71.

18. I hereby certify that the foregoing is true and correct

SIGNED

L. L. Bile

TITLE Lead Clerk

DATE December 15, 1971

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: