

C O P Y

(SUBMIT IN TRIPLICATE)

Indian Agency Window Rock

Arizona

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Allottee Harold Begay

Lease No. 14-20-603-1312

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	RECEIVED OCT 15 1956 U. S. GEOLOGICAL SURVEY
NOTICE OF INTENTION TO CHANGE PLANS.....	<input type="checkbox"/>	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	<input type="checkbox"/>	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL.....	<input type="checkbox"/>	SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	<input type="checkbox"/>	SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	<input type="checkbox"/>	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....	<input type="checkbox"/>		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

October 11, 1956

Well No. 1 is located 1980 ft. from N line and 660 ft. from Ex W line of sec. 25

C NW SW Sec. 25
(1/4 Sec. and Sec. No.)

25N
(Twp.)

11W
(Range)

NWPM
(Meridian)

Wildcat
(Field)

San Juan
(County or Subdivision)

New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is 6611.0 ft. GL

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

It is planned to set approximately 175 ft. of 10-3/4" OD surface casing and circulate cement to surface. It is then planned to drill with conventional rotary tools and mud to an approximate total depth of 5300 ft. The Gallup sand will be cored, and drill stem tested if the core indicates commercial productivity. Electric and micrologs will then be run. If commercial oil shows are encountered 5-1/2" OD 14# J-55 seamless casing will be set through the pay section and cemented with 200 sacks of regular cement. Gamma Ray logs will be run and the well will be selectively perforated and sand-oil fraced for completion.

If the well is a dry hole, it will be plugged in accordance with State rules and regulations.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.


Company Anderson-Prichard Oil Corporation

Address 1740 Broadway

Denver, Colorado

By KARL A. BASHAR

Title District Superintendent



C O P Y

NEW MEXICO
OIL CONSERVATION COMMISSION

Form C-128

Well Location and/or Gas Proration Plat

Date _____

Operator ANDERSON - FRICHARD OIL CORPORATION Lease HAROLD BEGAY

Well No. _____ Section 25 Township 25 NORTH Range 11 WEST, NMPM

Located 1980 Feet From the SOUTH Line, 660 Feet From the WEST Line,

SAN JUAN County, New Mexico. G. L. Elevation 6611.0 UNGRADED.

Name of Producing Formation _____ Pool _____ Dedicated Acreage _____

(Note: All distances must be from outer boundaries of Section)

		25	

660' 0

1980'

NOTE

This section of
form is to be
used for gas
wells only.



SCALE: 1"=1000'

1. Is this Well a Dual Comp. ? Yes ☐ No ☐.
2. If the answer to Question 1 is yes, are there any other dually completed wells within the dedicated acreage? Yes ☐ No ☐.

This is to certify that the above plat was prepared from field notes of actual surveys made by me or under my supervision and that the same are true and correct to the best of my knowledge and belief.

Name _____
Position _____
Representing _____
Address _____

Date Surveyed 9 OCTOBER 1956
James P. Leese
Registered Professional Engineer and/or
Land Surveyor James P. Leese
N. Mex. Reg. No. 1463