

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on reverse side)

FIELD NO. 14-29-603-1312
14-29-603-1312

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Water Injection

2. NAME OF OPERATOR
Skelly Oil Company

3. ADDRESS OF OPERATOR
1860 Lincoln Street, Denver, Colorado 80203

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface
660' FWL & 1980' FSL Section 25-25N-11W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
6611' GR 6621' KB

5. FIELD NO. 14-29-603-1312

6. IF DIFFERENT FROM FIELD NO. OR OTHER NAME

7. FIELD NO. 14-29-603-1312

8. FARM OR LOT NAME

9. WELL NO.

10. FIELD AND TOOL OR WILDCAT
Bisti Lower Gallup

11. ACCT. T. R. M. OR O.R. AND SURVEY OR AREA
Section 25-25N-11W

12. COUNTY OR PARCEL 13. STATE
San Juan New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

XX

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDON WELL*

(Note: Report results of multiple completion on Well Completion or Recompletion Report and form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

All depths shown are from Ground Level.

This well has reached the economic limit and is no longer profitable to operate. Plans are to plug and abandon this well; plugging as follows:

First Plug - (4982'- 5082') 100' plug across the Gallup Zone Perfs. 5039-5047'

Second Plug- 50' inside of the 5-1/2" casing and 50' above where casing is shot in two

Third Plug - (1305'- 1455') 150' plug extending downward from above the Fruitland coal section across the Pictured Cliffs Sand

Fourth Plug- (540'- 640') 100' plug extending from 50' above to 50' below the bottom of the Ojo Alamo Sand

10 sacks of cement in top of surface casing with dry hole marker

18. I hereby certify that the foregoing is true and correct

SIGNED

L. L. Biles

TITLE

Lead Clerk

DATE

July 20, 1971

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: