

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on reverse side)

Form approved
Bureau No. 42 R1424
5. LEASE DESIGNATION AND AERIAL NO.

14-20-603-1378

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Navajo-Window Rock

7. UNIT AGREEMENT NAME

East Bisti Unit

8. FARM OR LEASE NAME

9. WELL NO.

45

10. FIELD AND POOL, OR WILDCAT

Bisti Lower Gallup

11. SEC., T., R., M., OR BEK. AND SURVEY OR AREA

Section 30-25N-10W

12. COUNTY OR PARISH 13. STATE

San Juan

New Mexico

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Skelly Oil Company

3. ADDRESS OF OPERATOR

1860 Lincoln Street, Denver, Colorado 80203

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)
At surface

2310' FSL & 1650' FEL Section 30-25N-10W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, OR, etc.)

6641' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

PULL OR ALTER CASING ☐

WATER SHUT-OFF ☐

REPAIRING WELL ☐

FRACTURE TREAT ☐

MULTIPLE COMPLETE ☐

FRACTURE TREATMENT ☐

RESETTING CASING ☐

SHOOT OR ACIDIZE ☐

ABANDON* ☒

SHOOTING OR ACIDIZING ☐

ABANDONMENT* ☐

REPAIR WELL ☐

CHANGE PLANS ☐

(Other) ☐

(NOTE: Report results of multiple completion of well Completion or Recompletion Report and Log (form).)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of completion and proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

All depths shown are from Ground Level.

This well has reached the economic limit and is no longer profitable to operate. Plans are to plug and abandon this well; plugging as follows:

First Plug - (5053'- 5153') 100' plug across the Gallup Zone Perfs. 5146-5152'

Second Plug- 50' inside of the 5-1/2" casing and 50' above where casing is shot in two

Third Plug - (1400'- 1550') 150' plug extending downward from above the Fruitland coal section across the Pictured Cliffs Sand

Fourth Plug- (680'- 780') 100' plug extending from 50' above to 50' below the bottom of the Ojo Alamo Sand

10 sacks of cement in top of surface casing with dry hole marker

18. I hereby certify that the foregoing is true and correct

SIGNED

Le. J. Bish

TITLE

Lead Clerk

DATE

July 16, 1971

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: