

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE\*  
(Other instructions on re-  
verse side)Form Approved  
Budget Project No. 42 R1424  
U. S. GEOLOGICAL SURVEY AND SERIAL NO.

14-20-603-1366

6. IF T. OR A. AFFECTED BY TRIBE NAME

Navajo-Uska-Ye-Nu-Yah

7. UNIT AGREEMENT NAME

East Bisti Unit

8. FARM OR LEASE NAME

9. WELL NO.

37

10. FIELD AND TOOL, OR WILDCAT

Bisti Lower Gallup

11. SEC. T. R. M. OR DE. AND  
SURVEY OR AREA

Section 30-25N-10W

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS  
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Skelly Oil Company

3. ADDRESS OF OPERATOR

1860 Lincoln Street, Denver, Colorado 80203

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

1980' FNL &amp; 1980' FEL Section 30-25N-10W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6612.5' GR

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

FULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

XX

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion or recompletion operations on this form.)  
Completion or Recompletion Report and Log Form

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated and actual dates, for all operations proposed or completed on this work.) \*

All depths shown are from Ground Level.

This well has reached the economic limit and is no longer profitable to operate.  
Plans are to plug and abandon this well; plugging as follows:

First Plug - ( 5040'- 5140' ) 100' plug across the Gallup Zone Perfs. 5094-5132'

Second Plug- 50' inside of the 5-1/2" casing and 50' above where casing is shot in two

Third Plug - ( 1385'- 1535' ) 150' plug extending downward from above the Fruitland  
coal section across the Pictured Cliffs SandFourth Plug- ( 660'- 760' ) 100' plug extending from 50' above to 0' below the  
bottom of the Ojo Alamo Sand

10 sacks of cement in top of surface casing with dry hole marker

18. I hereby certify that the foregoing is true and correct

SIGNED

G. L. Byle

TITLE

Lead Clerk

DATE

July 16, 1971

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side