

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

078679

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME (A.T. Bennett
Bennett Federal (Western)

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Ballard Pictured Cliffs

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Section 25-25N-2W,

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

1. OIL ☐ GAS ☒
WELL WELL OTHER

2. NAME OF OPERATOR

Simclair Oil & Gas Company

3. ADDRESS OF OPERATOR

901 Lincoln Tower Bldg., 1850 Lincoln Street, Denver, Colo.

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

790' 2/North line and 790' 2/East line Sec. 25-25N-2W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6573 G.L.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

This well drilled in 1957 to TD 2250', 5-5/8" OD 2 1/2" casing set at 96', 5-1/2" 15.5" casing set at 2250', Pictured Cliffs perforated 2124' to 2150'. This well produced only 117 MCF during year of 1965. The last six months were as follows: July 1 MCF, August 0, September 6 MCF, October 2 MCF, November 0, December 7 MCF. The well was free treated at completion, and additional treatment does not appear to be beneficial.

It is proposed to spot 15 sack cement plug above perforations (2124-50') from 2100' - 1900' and 10' cement plug in top of casing with regulation 4" marker, clean and abandon location. (5-1/2" casing is not to be pulled.)

RECEIVED

JAN 26 1966

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

18. I hereby certify that the foregoing is true and correct

SIGNED

F. Haskin

TITLE Area Supervisor

DATE

January 25, 1966

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

RECEIVED

JAN 27 1966

CON. COM.

DATE

*See Instructions on Reverse Side