Forr (A)	26		
		·I	
	 	í	

## (SUBMIT IN TRIPLICATE)

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Indian Agency
Arimona
Allottee Contr. #11-20-603-1430
Lease No. Tract 139
Ken-No-To

	NOTICES AND	REPUR	IS ON WEL	LS
TICE OF INTENTION TO DRILL	s	UBSEQUENT REPOR	OF WATER SHUT-OFF	
OTICE OF INTENTION TO CHANGE P	<u> </u>	UBSEQUENT REPOR	OF SHOOTING OR ACIDI	ZING
OTICE OF INTENTION TO TEST WATE		-	of ALTERING CASING	i i
OTICE OF INTENTION TO REDRILL O			FOF REDRILLING OR REP	
OTICE OF INTENTION TO SHOOT OR NOTICE OF INTENTION TO PULL OR A	3		LL HISTORY.	
OTICE OF INTENTION TO ABANDON	: 1		LL HISTORY	A*
(INDICAT	E ABOVE BY CHECK MARK NATURI	OF REPORT, NOTIC	E, OR OTHER DATA)	
	****	June	10	, 19 <b>.59</b>
A No. 1 is loc A No. 1 is loc (M Sec. and Sec. No.)  Sti Lover Callup	258 11W (Twp.) (Rang	7 N	ft. from li  (Meridian)  New Fexice	
(Field)	(County or Subd	ivision)	(State or Te	rritory)
ne elevation of the derrick	C	seuli c. a	at.	San
le elevation of the derrick	Hoor above sea level is	15.2.11 11.		to the second
	DETAILS C	F WORK	à	
			7	
ate names of and expected depths to	o objective sands; show sizes, weig	hts, and lengths of	proposed casings; indicate	mudding jobs, centent
ate names of and expected depths to	o objective sands; show sizes, weig ing points, and all other in	hts, and lengths of portant proposed v	proposed casings; indicate vork)	mudding jobs, centent
		hts, and lengths of portant proposed v	proposed casings; indicate vork)	DIST. 3
7D: 5128 Perfora	objective sands; show sizes, weig ing points, and all other in	hts, and lengths of portant proposed v	proposed casings; indicate vork)	mudding jobs, colonial
TD: 5128 Perform TD: 5096 opose to mill well w P top allowable. If g. Frecture treat w	viso erude. Perfor well does not make	rate 5063-5 e top allow	675 w/k SFF. 3	Sueb well in &
opose to kill well were top allowable. If og. Fracture treat will a put on production production of work by the put of the put of work by the put of the put of work by the put of the put	/lse crude. Perfor well does not make /30,000 gals lse.	rate 9063-5 e top allow er.de 8 30,	075 w/k SFF. 3 mble, kill well 000 10/20 mee	Sweb well in & L v/lee crude & cand, Clean
TD: 5128 Perfora TD: 5096  spece to kill well w r top allowable. If g. Frecture treat w ll & put on production  understand that this plan of work  mpany ————————————————————————————————————	/lso crude. Performent well does not make /30,000 gals lse.	rate 9063-5 e top allow er.de 8 30,	075 w/k SFF. 3 mble, kill well 000 10/20 mee	Sweb well in & L v/lee crude & cand, Clean