UNITED STATES DEPARTMENT OF THE INTERIOR Verse hide)

SUBMIT IN TRIPLICATES

56 42 R1121 14-20-60 -1384

GEOLOGICAL SURVEY

SUNDRY	NOTICES	AND	REPORTS	ON	WFLIS
JU11011	1 10 1100	/ \l \u		\sim	T T L. L. L

(De ast use this form for proposals to drill or to deepen or plug back to a different reservoir, Use "APPLICATION FOR PERMIT-" for such proposals.)

Window Roe , Arizona 7. 1941 Acr - - - 697

6. IN TUDIES, ACTORS & CO. TROP MANIE

last Birti Unit B. PARM OR DEARE NAME

Skelly Oil Company

NAME OF OFFRATOR

3. ADDRESS OF OPERATOR 1860 Lincoln Street, Denver, Colorado

OTHER

32 tocation of well. (Report location clearly and in accordance with any State requirements.* See also space 17 below.)

9. WELL NO.

10, FIRED AND COOL, OR STREEAT

Bistl Lover Gallup 11. BEC., T., R., M., OR SHA. AND BURYET OR AREA

2310 330 -1882' FNL & 660' FWL Section 25-25N-11W

Section 25-25N-11W

14. PERMIT NO. 15. ELEVATIONS (Show whether DF, AT, GR, etc.) 6572' GR

12. COUNTY OR PARISH; 13. STATE San Juan

Hew Mexico

16.

At surface

6585' KB Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO: TEST WATER SHUT-OFF PULL OR ALTER CASING PRACTURE TREAT MULTIPLE COMPLETE XX ABANDON⁴

WATER SHUT-OFF REPAIRING WELL FRACTURE TREATMENT ALTERING CASING MHOOTING OR ACIDIZING AR UNDGNMENT*

SHOOT OR ACIDIZE REPAIR WELL (Other)

CHANGE PLANS (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

All depths shown are from Ground Level.

This well has reached the economic limit and is no longer profitable to operate. Plans are to plug and abandon this well; plugging as follows:

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and sones pertinent to this work.) *

First Plug - (5020'- 5120') 100' plug across the Gallup Zone Perfs. 5053-5088'

Second Plug- 50' inside of the 5-1/2" casing and 50' above where casing is shot in two

Third Plug - (1325'- 1475') 150' plug extending downward from above the F uitland coal section across the Pictured Cliffs Sand

Fourth Plug- (590'- 690') 100' plug extending from 50' above to 50' below the bottom of the Ojo Alamo Sand

10 sacks of cement in top of surface casing with dry hole marker

18.	I	hereby	certify	that	the	foregoing	is	true	and	correct

Lead Clerk

(This space for Federal or State office use)

APPROVED BY CONDITIONS OF APPROVAL, IF ANY: