



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe, N. M.
Lease No. 11078064
Unit Garson Unit

RECEIVED
JUL 1 1959

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

July 1, 1959

Well No. 34-24 is located 680 ft. from S line and 1200 ft. from E line of sec. 24

34-24 (1/4 Sec. and Sec. No.) 34 (Twp.) 12N (Range) P.M.M. (Meridian)
Disti (Field) San Juan (County or Subdivision) New Mexico (State or Territory)

The elevation of the surface above sea level is 6461 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mud, cement, and all other important proposed work)

6-17-59

6-17-59 ran and cemented (1.0") 8-5/8", 24", 3-5" casing at 109' with 100
to 121 cu. ft. Portland Cement, treated with 2% calcium chloride,
6-17-59 surface temperature 90° F., formation temperature 70° F. Estimated
strength after 12 hours 1100 psi. Flanged up and waited on cement.
Tested bit and casing with 700 psi., ok.

ILLEGIBLE

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Shell Oil Company

Address 705 West Municipal Drive

Alamogordo, New Mexico

By B. W. Shepard
Title Exploitation Engineer