

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE*
(Other instructions on reverse side)1. FOR ADDRESS, Contact Bureau No. 12 R1424
2. LEASE OR DEED NO. AND RECORD NO.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐		7. UNIT AGREEMENT NAME East Bisti Unit	
2. NAME OF OPERATOR Skelly Oil Company		8. FARM OR LEASE NAME	
3. ADDRESS OF OPERATOR 1860 Lincoln Street, Denver, Colorado 80203		9. WELL NO. 26	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' FSL & 1973' FEL Section 24-25N-11W		10. FISHING HOLE NO. (If any) Fish Hole - Gallup	
14. PERMIT NO.		15. ELEVATIONS (Show whether DF, RT, or, etc.) 6560' GR	
		12. COUNTY OR PARISH 13. STATE San Juan New Mexico	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
STOP WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	WATER SHUT-OFF ☐	ABANDON ☐
FRACURE TREAT ☐	MULTIPLE COMPLETE ☐	FRACURE TREATMENT ☐	ACIDIZING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☒	SHOOTING OR ACIDIZING ☐	ACIDIZING ☐
REPAIR WELL ☐	CHANGE PLANS ☐	(Other) ☐	(Other) ☐
(Other) ☐		(NOTE: Report results of multiple completion or well Completion or Recompletion Report and Log Form)	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

All depths shown are from Ground Level.

This well has reached the economic limit and is no longer profitable to operate. Plans are to plug and abandon this well; plugging as follows:

First Plug - (5042'- 5142') 100' plug across the Gallup Zone Perfs. 5043-5116'

Second Plug- 50' inside of the 5-1/2" casing and 50' above where casing is shot in two

Third Plug - (1335'- 1485') 150' plug extending downward from above the Fruitland coal section across the Pictured Cliffs Sand

Fourth Plug- (610'- 710') 100' plug extending from 50' above to 50' below the bottom of the Ojo Alamo Sand

10 sacks of cement in top of surface casing with dry hole marker

18. I hereby certify that the foregoing is true and correct

SIGNED L. L. BilesTITLE Lead Clerk

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY: _____

TITLE _____

DATE _____

