

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved
Budget Bureau No. 42-R1424
6. LEASE DESIGNATION AND SERIAL NO.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	7. UNIT AGREEMENT NAME East Blati Unit
2. NAME OF OPERATOR Skelly Oil Company	8. FARM OR LEASE NAME
3. ADDRESS OF OPERATOR 1860 Lincoln Street, Denver, Colorado 80203	9. WELL NO. 24
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 6560' FSL & 2080' FEL, Section 19-25N-10W	10. FIELD AND LOCATION OF WELLCAT Blati Lower Gallup
14. PERMIT NO.	15. ELEVATIONS (Show whether DP, RT, OR, etc.) 6574' GR
11. SECTION, TOWNSHIP, RANGE, AND SURVEY OR OTHER DATA Section 19-25N-10W	12. COUNTY OR PARISH San Juan
	13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

XX

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and any other pertinent data.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimates of cost, for any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all points pertinent to this work.)*

All depths shown are from Ground Level.

This well has reached the economic limit and is no longer profitable to operate.
Plans are to plug and abandon this well; plugging as follows:

First Plug - (5066'- 5166') 100' plug across the Gallup Zone Perfs. 5077-5155'

Second Plug- 50' inside of the 5-1/2" casing and 50' above where casing is shot in two

Third Plug - (1375'- 1525') 150' plug extending downward from above the Fruitland
coal section across the Pictured Cliffs SandFourth Plug- (650'- 750') 100' plug extending from 50' above to 50' below the
bottom of the Ojo Alamo Sand

10 sacks of cement in top of surface casing with dry hole marker

18. I hereby certify that the foregoing is true and correct

SIGNED

L. L. Bishop

TITLE

Lead Clerk

DATE

July 16, 1971

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: