UNITED STATES DEPARTMENT OF THE INTERIOR (Other Instructions on re-

	GEO	14-20-603-1380			
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)				G. IF INDIAN, ALLOTTEE OR TRIBE NAME Window Rock	
1.	WELL X WELL OTHER	7. UNIT AGREEMENT NAME			
WELL (A) WELL OTHER 2. NAME OF OPERATOR				East Bisti Unit	
	Skelly Oil Company				
3. ADDRESS OF OPERATOR 1860 Lincoln Street, Denver, Colorado 80203				9. WELL NO.	
4.	LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface			10. FIELD AND POOL, OR WILDCAT Bisti Lower Gallup	
	660' FSL & 1980' FEL Section 22-25N-11W			11. SEC., T., R., M., OR BLE, AND SURVEY OR AREA	
14.	PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.)		. RT. GR. etc.)	Section 22-	25N-11W
		6485' GR	,,,	San Juan	New Mexico
16.	Check Appro	opriate Box To Indicate N	Nature of Notice, Report, or C	other Data	
				ENT REPORT OF:	
	TEST WATER BRUT-OFF PULL	L OR ALTER CASING	WATER SHUT-OFF	REPAIRING WI	ELL,
	FRACTURE TREAT MUL	TIPLE COMPLETE	FRACTURE TREATMENT	ALTERING CAS	IING
	 	NDON*	SHOOTING OR ACIDIZING	ABANDONMENT	
	(Other)	NGE PLANS	(Other)(Note: Report results	of multiple completion of etion Report and Log form	n Well
	proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* This well has reached the economic limit and is no longer profitable to operate. Plans are to plug and abandon this well; plugging as follows: First Plug - 100' plug across Gallup Zone perforations 4923-4960' Second Plug - 50' inside the 5-1/2" casing and 50' above where casing is shot in two Third Plug - 150' cement plug extending downward from above the Fruitland Coal section across the Pictured Cliffs Sand Fourth Plug - 100' plug at bottom of Ojo Alamo Sand (unless surface casing is set				
	through the Ojo Alamo Sand) 10 sacks of cement in top of surface casing with dry hole marker				
	TO SACKS OF CEME	it in top of surra	ce casing with dry ho	JUN 1 7 1971	
18.	I hereby certify that the for golog is tru	le and correct	trict Operations Supt	OIL CON. COM. DIST. 3	
=	(This appear for Wednes) - Said S		criec oberactions supe.	DATE June	10, 1971
	(This space for Federal or State office un	ne) (
	APPROVED BY	TITLE		DATE	