

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.
PERMIT NO.

14-20-603-1439

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input checked="" type="checkbox"/> Water Supply		6. IF INDIAN, ALLOTTEE OR TRIBE NAME Navajo Tribe	
2. NAME OF OPERATOR Skelly Oil Company		7. UNIT AGREEMENT NAME East Bisti Unit	
3. ADDRESS OF OPERATOR 1860 Lincoln Street - Denver, Colorado 80203		8. FARM OR LEASE NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 990' FSL and 330' FEL Section 23, T 25 N, R 11 W		9. WELL NO. 28	
14. PERMIT NO.		10. FIELD AND POOL, OR WILDCAT Bisti Lower Gallup	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6567' KB		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 23-25N-11W	
		12. COUNTY OR PARISH San Juan	13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

X

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

All depths shown are from Ground Level.

Plans are to Plug and Abandon this well, plugging as follows:

Present cement behind casing is from 700' to 330'.

Plug inside casing from 625' to 450'.

100' cement plug, 50 inside casing stub and 50' above where casing is shot in two.

10 sacks of cement in top of surface casing with dry hole marker.

18. I hereby certify that the foregoing is true and correct

SIGNED

L. L. Byles

TITLE

Lead Clerk

DATE

September 23, 1971

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

DATE

