

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

RECEIVED  
BLM

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

W.M. GALLAWAY

3. Address and Telephone No.

3005 NORTHRIDGE, SUITE I, FARMINGTON, NM 87401 (505) - 325-6771

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

2310' FNL & 2310' FEL, ( UNIT G)  
SEC.23, T23N, R11W NMPM

5. Lease Designation and Serial No.

14-20-603-1349

6. If Indian, Allottee or Tribe Name

NAVAJO-ALLOTTED

7. If Unit or CA, Agreement Designation

8. Well Name and No.

BITTONEY NEZ # 1

9. API Well No.

30-045-05283

10. Field and Pool, or Exploratory Area

BISTI LOWER GALLUP

11. County or Parish, State

SAN JUAN COUNTY, NM

CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☐ Other  
☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☒ Water Shut-Off  
☒ Conversion to Injection  
☒ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

WORK WAS PERFORMED ON MAY 17, 1996

1. SET WIRE LINE CAST IRON BRIDGE. PLUG @ 4625'
2. SPOTTED 190' OF CEMENT ON TOP OF PLUG THROUGH 2-3/8" TBG
3. SPOTTED CEMENT PLUG FROM INSIDE 5-1/2" CSG FROM 2890' TO 2790' THROUGH 2-3/8" TBG
4. PERFORATE CSG AT 1482' SPOTTED CEMENT PLUG FROM 1482' TO 1050', SQUEEZED AT 500 LBS. BALANCE PLUG THROUGH 2-3/8" TBG. SHUT IN FOR ONE HOUR. 5 psi DROP IN PRESSURE.
5. PERFORATE CSG AT 696', BROKE CIRCULATION THROUGH 2-3/8" TBG LOCKED UP. CEMENTED INSIDE 5-1/2" CSG TO SURFACE WITH 2-3/8" TBG. CUT OFF WELLHEAD
6. RAN 63' OF 1" TBG AND CEMENTED TO SURFACE BETWEEN 8-5/8" SURFACE AND 5-1/2" CSG
7. ERECTED DRY HOLE MARKER
8. CLEANED LOCATION

14. I hereby certify that the foregoing is true and correct

Signed

*W.M. Gallaway*

Title

OPERATOR

Date

6-17-96

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

DATE