

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir,
Use "APPLICATION FOR PERMIT--" for such proposals.

SUBMIT IN TRIPLICATE

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.

SF 078061

6. If Indian, Allottee or Tribe Name

7. If Unit or CA. Agreement Designation

Carson Unit

8. Well Name and No.

Carson Unit No. 4-2

9. API Well No.

30-045-05314

10. Field and Pool, or Exploratory Area

Bisti Lower Gallup

11. County or Parish, State

San Juan, New Mexico

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

☒ Notice of Intent

☐ Subsequent Report

☐ Final Abandonment Notice

☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Central Resources, Inc. intends to plug the well in accordance with regulations. Production equipment will be removed and the well will be plugged as specified. **Perforate and squeeze will be used unless casing can be recovered over the specified interval or there is evidence cement is in place behind the casing.**

Proposed procedure:

- Notify the Farmington BLM office at 505-599-8907 24 hours prior to commencement of plugging operations.
- Pull all retrievable downhole production equipment.
- Set a CIBP at 4815' and spot 50' of cement on top at top of Lower Gallup at 4821'.
- Spot a 100' cement plug from 3925' to 3825' across the top of the Mancos at 3875'.
- Spot a 100' cement plug from 2085' to 2985' across the top of the Menefee at 2035'.
- Spot a 100' cement plug from 1260' to 1160' across the top of the Pictured Cliffs at 1210'.
- Spot a 278' cement plug from 278' to surface across the surface casing shoe at 228'.
- Cut wellhead and install dry hole marker. Clear and remediate location.

Please take into account the number of existing P&A procedures, the number of P&A procedures you have requested and the available equipment and allow Central Resources, Inc. until the end of 2001 to complete this abandonment.

14. I hereby certify that the foregoing is true and correct

Signed Rodney L Seale
Rodney L Seale

Title District Manager

Date June 28, 2000

(This space for Federal or State office use)

Approved by _____

Title _____

Date 8/23/00

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any manner within its jurisdiction.

*See Instruction on Reverse Side

CENTRAL RESOURCES, INC.

Carson Unit No. 4-20

Review Date:

02-20-96 BY CRI

Elevation: 6403'GL, 6414'KB

Location: 1850' FWL, 660' FNL, Sec 20,
25-N, 11-W, San Juan County,
New Mexico

Field: Bisti Lower Gallup

Zone: Lower Gallup

Perfs: 4826'-4984'

Spud Date: September 10, 1956

