16.

UNITED STATES SEBMIT IN TRIPLICATES DEPARTMENT OF THE INTERIOR (Other Instructions on re-UNITED STATES GEOLOGICAL SURVEY

Form approved, Budget Bureau No. 42 R1424. D. LEASE DESIGNATION AND BERIAL NO.

New Mexico

San Juan

	14	420) -6	03-	143	6			
ß	ır	IND	IAN.	ALLO	TTEE	OR	TRIBE	NAMI	E

	SUNDKY	Y NOTICES	ANU	KEPOKIS	ON '	WELLS	
Do not i	use this form	for proposals to	e drill or to	deepen or plug	back to	a different	reservo

(1

Use "APPLICATION FOR PERMIT—" for such proposals,)	Navajo Tribal			
WELL X WELL OTHER	7. UNIT AGREEMENT NAME East Bisti Unit			
Skelly Oil Company	8. FARM OR LEADE NAME			
1860 Lincoln Street, Denver, Colorado 80203	9. WELL NO.			
i. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)	10. FIELD AND POOL, OR WILDCAT			
660' FNL & 1980' FWL Section 21-25N-11W	Bisti Lower Gallup 11. BEC., T., R., M., OR BLK. AND HURVET OR AREA			
14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.)	Section 21-25N-11W			

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO.					BUBGAYORAL BEFORE OF.				
			·			,		(
TEST WATER SHUT-OFF		PULL OR ALTER CASING			WATER SHUT-OFF	•		REPAIRING WELL	
FRACTURE TREAT		MULTIPLE COMPLETE			PRACTURE TREAT	MENT	!	ALTERING CASING	
SHOOT OR ACIDIZE		ABANDON*	<u>X</u>		SECOTING OR ACI	IDIZING		ABANDON MENT*	
REPAIR WELL		CHANGE PLANS			(Other)			·	
(Other)					(Note: Rep Completion	port rest or Reco	ilts of mplet	l multiple completion on Well ion Report and Log form.)	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and some pertinent to this work.) *

This well has reached the economic limit and is no longer profitable to operate. Plans are to plug and abandon this well; plugging as follows:

First Plug - 100' plug across Gallup Zone perforations 4938-4972'Second Plug - 50' inside the 5-1/2'' casing and 50' above where casing is shot in two Third Plug - 150' cement plug extending downward from above the Fruitland Coal section across the Pictured Cliffs Sand

Fourth Plug - 100' plug at bottom of Ojo Alamo Sand (unless surface casing is set through the Ojo Alamo Sand)

10 sacks of cement in top of surface casing with dry hole marker



	·		DIST	. 3
SIGNED SIGNED	TITLE DI	strict Operations	Supt. DATE	June 10, 1971
(This space for Federal or State office use)	<i>0</i>		1	-
CONDITIONS OF APPROVAL, IF ANY:	TITLE		DATE	· <u>**</u>