

(SUBMIT IN TRIPLICATE)

Land Office **Santa Fe, N.M.**
Lease No. **SF-078066**
Unit _____

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO PERFORATE AND SAND OR SHOOT OR ACIDIZE FRAC	X	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	X		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

June 7, 1956

Government
Well No. **14-15** is located **660** ft. from **[S]** line and **660** ft. from **[W]** line of sec. **15**
SW/4 SW/4 15 **25 N. 12 W.** **N.M.P.M.**
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Blasi **San Juan** **New Mexico**
(Field) (County or Subdivision) (State or Territory)

The elevation of the **Kelly Bushing** above sea level is **6254** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Present Status: Depth: **4875'**
Surface Casing: **8 5/8" at 219'**
Hole Size: **7 7/8" hole 219' to 4875'**

Proposed Work:

1. Run and cement **5-1/2"** casing at **4870'** with 200 sacks
2. Clean out to **4840'**.
3. Perforate **4 1/2"** holes per ft. **4820-4802** and **4777-4760** (**39'-10** holes).
4. Sand oil frac. with 30,000 gals. oil and 50,000 gals. **CON. COM.**
5. Set drillable bridge plug at **4782'**.
6. Perforate **4 1/2"** holes per ft. **4776-4741'** (**35'-10** holes) **3** (over)

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **Shell Oil Company**
Address **33 Richards Street**
Salt Lake City, Utah

By **B. W. Shepard**
Title **Exploitation Engineer**

7. Sand oil frac. with 30,000 gals. oil and 50,000# sand.
8. Set drillable bridge plug at 4735'.
9. Perforate 4 1/2" holes per ft. 4723-4705'. (18'-72 holes)
10. Sand oil frac. with 15,000 gals. oil and 23,000# sand.
11. Clean out plugs. Make production test.
12. Install Christmas Tree or artificial lift equipment.