17 X

## (SUBMIT IN TRIPLICATE)

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Budget Bureau No.	42-R358.4.
Form Approved.	J. American

Land Office Santa Fe, NaMe

SF-078061

Unit Carson

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO CHANGE PLANS.  NOTICE OF INTENTION TO CHANGE PLANS.  NOTICE OF INTENTION TO TEST WATER SHUT-OFF.  NOTICE OF INTENTION TO TEST WATER SHUT-OFF.  NOTICE OF INTENTION TO RE-DRILL OR REPAR WELL.  NOTICE OF INTENTION TO SHOOT OR ACIDIZE.  NOTICE OF INTENTION TO SHOOT OR ACIDIZE.  NOTICE OF INTENTION TO PULL OR ALTER CASING.  NOTICE OF INTENTION TO PULL OR ALTER CASING.  NOTICE OF INTENTION TO ABANDON WELL.  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  JANUARY 19  Well No. 24-17 is located ft. from (Kaney) (Meridian)  SE SW 17 25 N 11 W NAME  (Kaney) (Meridian) New Next  (Field) (County or Subdivision) (State or Territo  The elevation of the deflication above sea level is 6356-41.  DETAILS OF WORK  State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate meridian may be conversion. Work ing points, and all other important proposed work)  DETAILS OF WORK  State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate meridian may be came clean, pulled. Ba:  DETAILS OF WORK  State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate meridian may be came clean, pulled. Ba:  DETAILS OF WORK  State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate meridian may be came clean, pulled. Ba:  B. Rah tubing with packer.  R. Pumped 60 bbls. of inhibited water down annulus to displace unit fluid. Set packer at the packer at	
Subsequent report of shooting or acidize notice of intention to test water shut-off notice of intention to respiral or repair well notice of intention to respiral or repair well notice of intention to shoot or acidize subsequent report of altering casing subsequent report of respiration notice of intention to shoot or acidize subsequent report of respiration notice of intention to pull or after casing notice of intention to pull or after casing subsequent report of respiration notice of intention to be after casing subsequent report of respiration or adaption well.    Converted to Injector   Converted to Injector	
Well No. 24-17 is located 660 ft. from SE WATER SHOTOR ACTION TO TEST WATER SHOTOR ACTION TO RE-DRILL OR REPAIR WELL NOTICE OF INTENTION TO SHOOT OR ACIDIZE NOTICE OF INTENTION TO PULL OR ALTER CASING NOTICE OF INTENTION TO ABANDON WELL SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR NOTICE OF INTENTION TO ABANDON WELL SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR SUBSEQUENT REPORT OF REPORT OF REPORT OF REPAIR SUBSEQUENT REPORT OF REP	√G I
Subsequent report of Re-Drilling or Repart Well Notice of Intention to Shoot or acidize.  Notice of Intention to Shoot or acidize.  Notice of Intention to Pull or After Casing.  Notice of Intention to Pull or After Casing.  Notice of Intention to Abandon Well.  (Indicate above by Check Mark Nature of Report, Notice, or other Data)  January 19  Well No. 24-17 is located 660 ft. from Siline and 1980 ft. from SE SW 17  25 N 11 N NAIPM  (Range) (Meridian) New Next  (Field) (County or Subdivision) (State or Territo State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mention work in points, and all other important proposed work)  State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mention work in points, and all other important proposed work)  DETAILS OF WORK  State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mention work in points, and all other important proposed work)  DETAILS OF WORK  State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mention work in points, and all other important proposed work)  Pressure tested tubing with 1000 psi for 15 minutes, OK.  Swabbed while running clean Point Lookout water (treated with Treated with Treated with Treated with Treated Swatch and T	
Well No. 24-17 is located 660 ft. from Spine and 1980 ft. from Well No. 25 N 11 N Normalian (Twp.) (Range) (Meridian) New Next (Country or Subdivision) (State or Territo State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate more respected while running clean Point Lookout water (treated with T detergent) down casing. After tubing became clean, pulled. Ba:  Ranged 60 bbls. of inhibited water down annulus to displace unit fluid. Set packer at 1834.	
Well No. 24-17 is located 660 ft. from S line and 1980 ft. from SE SW 17  Blet1 (Field) (County or Subdivision) (State or Territo Conversion Work    County or Subdivision   C	
Well No. 24-17 is located 560 ft. from S line and 1980 ft. from W line  SE SW 17  County or Subdivision (State or Territo  Kelly Bushing  The elevation of the defrict moor above sea level is 535-41.  DETAILS OF WORK  State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate m ing points, and all other important proposed work)  Pressure tested tubing with 1000 psi for 15 minutes, OK.  Swabbed while running clean Point Lookout water (treated with Tedetergent) down casing. After tubing became clean, pulled. Ba:  Ran tubing with packer.  Pumped 60 bbls. of inhibited water down annulus to displace unit fluid. Set packer at 334 and filled with inhibited water	
Well No. 24-17 is located 660 ft. from S line and 1980 ft. from W line  SE SW 17  25 N 11 W MAPPE  (County or Subdivision)  (County or Subdivision)  (State or Territo  Kelly Bushing  (Real expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate ming points, and all other important proposed work)  DETAILS OF WORK  State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate ming points, and all other important proposed work)  Pressure tested tubing with 1000 psi for 15 minutes, OK.  Swabbed while running clean Point Lockout water (treated with Tide tergent) down casing. After tubing became clean, pulled. Bath Ran tubing with packer.  Pumped 60 bbls. of inhibited water down annulus to displace unit fluid. Set packer at 4834 and filled with inhibited water	X
Well No. 24-17 is located 560 ft. from S line and 1980 ft. from W line  SE SW 17  Rieti (4 Sec. and Sec. No.)  Kelly Bushing (County or Subdivision)  Kelly Bushing (County or Subdivision)  Kelly Bushing (County or Subdivision)  Kelly Bushing (State or Territor State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate monographic or subdivision work (State or Territor State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate monographic or subdivision work (State or Territor State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate monographic or subdivision work (State or Territor State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate monographic or subdivision (State or Territor State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate monographic or subdivision (State or Territor State or Territor (State or Territor State or Territor (State or Territor (S	^
Well No. 24-17 is located ft. from S line and 1980 ft. from W line  SE SW 17  25 N 11 W Maips  (Meridian)  New Mexi  (Field)  Kelly Bushing  (County or Subdivision)  (State or Territo  A DETAILS OF WORK  State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate meridian work ing points, and all other important proposed work)  Details of minutes, OK.  Swabbed while running clean Point Lockout water (treated with Telegraph) down casing. After tubing became clean, pulled. Bails Ran tubing with packer.  Pumped 60 bbls. of inhibited water down annulus to displace unit fluid. Set packer at 4834 and filled with inhibited water	62
Bleti  (Field)  (County or Subdivision)  (State or Territo  Keily Bushing  (County or Subdivision)  (State or Territo  (State or Territo  DETAILS OF WORK  State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate months of months ing points; and all other important proposed work)  Pressure tested tubing with 1000 psi for 15 minutes, OK.  Swabbed while running clean Point Lookout water (treated with Tedetergent) down casing. After tubing became clean, pulled. Bash Ran tubing with packer.  Pumped 60 bbls. of inhibited water down annulus to displace unit fluid. Set packer at and filled with inhibited water	of sec. 17
(Field)  (County or Subdivision)  (State or Territo  Kelly Bushing  The elevation of the deflect hoor above sea level is 636.41.  DETAILS OF WORK  State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate months in grounds, and all other important proposed work)  Pressure tested tubing with 1000 psi for 15 minutes, OK.  Swabbed while running clean Point Lookout water (treated with Tedetergent) down casing. After tubing became clean, pulled. Bath Ran tubing with packer.  Pumped 60 bbls. of inhibited water down annulus to displace unit fluid. Set packer at 6334. and filled with inhibited water	
The elevation of the deflect hoof above sea level is	CO
DETAILS OF WORK  State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate monversion Work  Pressure tested tubing with 1000 psi for 15 minutes, OK.  Swabbed while running clean Point Lookout water (treated with Tester detergent) down casing. After tubing became clean, pulled. Base Ran tubing with packer.  Pumped 60 bbls. of inhibited water down annulus to displace unificial. Set packer at and filled with inhibited water.	y)
State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate monversion Work  Pressure tested tubing with 1000 psi for 15 minutes, OK.  Swabbed while running clean Point Lookout water (treated with Tester detergent) down casing. After tubing became clean, pulled. Base Ran tubing with packer.  Ran tubing with packer.  Pumped 60 bbls. of inhibited water down annulus to displace unif fluid. Set packer at	
Pressure tested tubing with 1000 psi for 15 minutes, OK.  Swabbed while running clean Point Lookout water (treated with Todetergent) down casing. After tubing became clean, pulled. Base Ran tubing with packer.  Pumped 60 bbls. of inhibited water down annulus to displace unit fluid. Set packer at	
Swabbed while running clean Point Lookout water (treated with Treated detergent) down casing. After tubing became clean, pulled. Bath Ran tubing with packer.  Pumped 60 bbls. of inhibited water down annulus to displace unit fluid. Set packer at	udding jobs, cement-
Ran tubing with packer.  Pumped 60 bbls. of inhibited water down annulus to displace unifiliad. Set packer at	
Pumped 60 bbls. of inhibited water down annulus to displace unifulid. Set packer at 4634 , and filled with inhibited water	iton X-100
and filled with inhibited water	
	hibited Will notif
I understand that this plan of work must receive approval in writing by the Geological Survey before operations may ompany	REFLYEN
ddress P. O. Box 1200	W22 1962
Parmington, N.M. W. M. MARCHAIL	CON. CO.
By By	TO COM /
Title Division Exploits	IST. 3