SHELL OIL COMPANY

Carson Unit WELL NO. 44-13

Bisti

BIZES___

(FIELD)

DRILLING REPORT FOR PERIOD ENDING

13

(SECTION OR LEASE)

San Juan, New Mexico

7-19-59

T 25 N. R 12 W

	(COUNTY)			7-19-59		T 25 N, R 12 W (TOWNSHIP OR RANCHO)					
DAY		DEPTHS				(Township or narcho)					
DAY	FROM		то	R	EMARKS						
				cation: 735' N and 73 N.M.P.M., Sar evations: GR 6412.28'	ouncy,	ner Section 13, T 25 N, R 12 W, New Mexico.					
				DF 6419.68' KB 6420.88'							
7-11 To 7-12	О	23	Go	Spudded 1:30 P.M. 7-11-59. Ran and cemented (97') 8-5/8", 24#, J-55 casing at 106' with 100 sacks cement treated with 2% calcium chloride. Good returns to surface. Flanged up and waited on cement. Pressure tested casing and BOP with 700 psi, OK.							
7-13 To 7-19	2327		4%	-/ - 1 / 1 / 1 / - / / - / / - / / - / / - / - / / - / / - / / - / - / / - / / - / - / / / - / / / - / / - / / / - / / / - / / / / / / - / / / / / / / / / / / / / / / / / / /		log. Ran and cemented (5004') h 150 sacks cement treated with ssure 1800 psi. Released rig					
				Checked BOP Daily Mud Summary WT 9-9.8#/gal. Vis 35-120 sec. WL 4.8-7.8 cc FC 2/32 pH 8.5							
	C	ONDITIO	ON AT BEG	INNING OF PERIOD	Contractor: Brinkerhoff Drilling Company						
	HOLE		CASING S	DEPTH SET	Drillers:	J. Speaker C. Adams					
SIZE	FROM	то			-	E. Babcock					
					Co. Pusher:	R. I. Alberts					

2-50 PRINTED IN U. S. A. 3-58 Preprint #M 1718-P 5-59

SHELL OIL COMPANY

Carson Unit 44-13 WELL NO.___

Bisti

San Juan, New Mexico

(FIELD)

DRILLING REPORT FOR PERIOD ENDING

(SECTION OR LEASE)

7-29-59

T 25 N, R 12 W

- 4.1	COUNT		T 25 N, R 12 W (TOWNSHIP OR RANCHO)
DAY	DEP	тнѕ	REMARKS
7–2 0	5025 (ID)		Perforated four 1/2" holes/ft. 4869-95, 4904-12, 4942-46, 4956-62, 4972-78.
7. -21			Spotted 200 gal. mud acid. Sand oil fractured with 50,000 gal. crude, l#/gal. sand, and 170 rubber balls. Breakdown pressure 2200-1100 psi. Maximum injection pressure 2150 psi, minimum injection pressure 2000 psi, pressure increased 100 psi after 120 balls, 50 psi after next 50 balls. Average injection rate 35 bbls/min.
722			Cleaned out frac sand 4955-5000'. Ran 2-3/8" tubing to 4893'.
7- 23			Ran rods and pump.
7-24 To 7-28			Pumped and recovered all load and frac oil, 1483 bbls.
729			INITTAL PRODUCTION Pumping 137 B/D grass, 137 B/D clean, 0.2% cut, 266 MCF/D gas, GOR 1940. Completed 7-29-59.

HOLE		CASING SIZE	DEPTH SET
FROM	то		
0	115	8-5/8"	106'
115	5025	4-1/2"	5013 '
	ŀ		
L	<u> </u>	_	
	FROM	FROM TO	FROM TO

