

RADIOACTIVITY LOG
ELEX JET SERVICES,

WELEX JET SERVICES, Inc.
 CENSORED BY: WELL SURVEYS, INC. FILE NO. _____

Well COMPANY HUERFANITO L

CO
DO

LICENSED BY: WELL SURVEYS, INC. FILE NO. _____																																																																																													
Location of Well COMPANY HUERFANITO DRILLING COMPANY WELL PAYNE # 3-14 FIELD SOUTH KUTZ ✓ COUNTY SAN JUAN ✓ STATE NEW MEXICO LOCATION 840' PSL & 1760' FEL SECTION 1425N 8W	COMPANY HUERFANITO DRILLING CO. WELL PAYNE # 3-14 FIELD SOUTH KUTZ ✓ COUNTY SAN JUAN ✓ STATE NEW MEXICO LOCATION 840' PSL & 1760' FEL SECTION 1425N 8W																																																																																												
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%; padding: 5px;"> LOG MEAS. FROM KELLY BUSHING (0' ABOVE GROUND LEVEL) DRLG. MEAS FROM KELLY BUSHING (0' ABOVE GROUND LEVEL) </td> <td style="width: 50%; padding: 5px;"> ELEV. 6776 ELEV. 6776 </td> </tr> <tr> <td style="padding: 5px;"> PERM. DATUM GROUND LEVEL </td> <td style="padding: 5px;"> ELEV. 6768 </td> </tr> </table>		LOG MEAS. FROM KELLY BUSHING (0' ABOVE GROUND LEVEL) DRLG. MEAS FROM KELLY BUSHING (0' ABOVE GROUND LEVEL)	ELEV. 6776 ELEV. 6776	PERM. DATUM GROUND LEVEL	ELEV. 6768																																																																																								
LOG MEAS. FROM KELLY BUSHING (0' ABOVE GROUND LEVEL) DRLG. MEAS FROM KELLY BUSHING (0' ABOVE GROUND LEVEL)	ELEV. 6776 ELEV. 6776																																																																																												
PERM. DATUM GROUND LEVEL	ELEV. 6768																																																																																												
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th style="width: 40%;">TYPE OF LOG</th> <th style="width: 30%;">GAMMA RAY</th> <th style="width: 30%;">NEUTRON</th> <th style="width: 20%;"></th> </tr> <tr> <td>RUN NO.</td> <td>1</td> <td>1</td> <td></td> </tr> <tr> <td>DATE</td> <td>11-1-55</td> <td>11-1-55</td> <td></td> </tr> <tr> <td>JOB NO.</td> <td>46-1502</td> <td>46-1502</td> <td></td> </tr> <tr> <td>TOTAL DEPTH (DRILLER)</td> <td>2450</td> <td>2450</td> <td></td> </tr> <tr> <td>EFFECTIVE DEPTH (DRILLER)</td> <td>2450</td> <td>2450</td> <td></td> </tr> <tr> <td>TOTAL DEPTH (R/A LOG)</td> <td>2450</td> <td>2450</td> <td></td> </tr> <tr> <td>TOP OF LOGGED INTERVAL</td> <td>100</td> <td>100</td> <td></td> </tr> <tr> <td>BOTTOM OF LOGGED INTERVAL</td> <td>2448</td> <td></td> <td></td> </tr> <tr> <td>FLUID IN HOLE</td> <td>DRY</td> <td>DRY</td> <td></td> </tr> <tr> <td>FLUID LEVEL</td> <td>2447</td> <td>2444</td> <td></td> </tr> <tr> <td>MAXIMUM RECORDED TEMPERATURE</td> <td></td> <td>800N</td> <td></td> </tr> <tr> <td>NEUTRON SOURCE STRENGTH & TYPE</td> <td></td> <td>3.75</td> <td></td> </tr> <tr> <td>SOURCE SPACING—IN.</td> <td></td> <td>10</td> <td></td> </tr> <tr> <td>LENGTH OF MEASURING DEVICE—IN.</td> <td>30</td> <td>2 5/8</td> <td></td> </tr> <tr> <td>O.D. OF INSTRUMENT—IN.</td> <td>5 0</td> <td>4 0</td> <td></td> </tr> <tr> <td>TIME CONSTANT—SECONDS</td> <td>20</td> <td>20</td> <td></td> </tr> <tr> <td>LOGGING SPEED FT./MIN.</td> <td>5"</td> <td>50</td> <td></td> </tr> <tr> <td></td> <td>2"</td> <td>0.7</td> <td></td> </tr> <tr> <td>STATISTICAL VARIATION—IN.</td> <td>275</td> <td>0.5</td> <td></td> </tr> <tr> <td>SENSITIVITY REFERENCE</td> <td></td> <td>275</td> <td></td> </tr> <tr> <td>RECORDED BY</td> <td>BARRON</td> <td>BARRON</td> <td></td> </tr> <tr> <td>WITNESSED BY</td> <td>ROHME</td> <td>ROHME</td> <td></td> </tr> </table>		TYPE OF LOG	GAMMA RAY	NEUTRON		RUN NO.	1	1		DATE	11-1-55	11-1-55		JOB NO.	46-1502	46-1502		TOTAL DEPTH (DRILLER)	2450	2450		EFFECTIVE DEPTH (DRILLER)	2450	2450		TOTAL DEPTH (R/A LOG)	2450	2450		TOP OF LOGGED INTERVAL	100	100		BOTTOM OF LOGGED INTERVAL	2448			FLUID IN HOLE	DRY	DRY		FLUID LEVEL	2447	2444		MAXIMUM RECORDED TEMPERATURE		800N		NEUTRON SOURCE STRENGTH & TYPE		3.75		SOURCE SPACING—IN.		10		LENGTH OF MEASURING DEVICE—IN.	30	2 5/8		O.D. OF INSTRUMENT—IN.	5 0	4 0		TIME CONSTANT—SECONDS	20	20		LOGGING SPEED FT./MIN.	5"	50			2"	0.7		STATISTICAL VARIATION—IN.	275	0.5		SENSITIVITY REFERENCE		275		RECORDED BY	BARRON	BARRON		WITNESSED BY	ROHME	ROHME	
TYPE OF LOG	GAMMA RAY	NEUTRON																																																																																											
RUN NO.	1	1																																																																																											
DATE	11-1-55	11-1-55																																																																																											
JOB NO.	46-1502	46-1502																																																																																											
TOTAL DEPTH (DRILLER)	2450	2450																																																																																											
EFFECTIVE DEPTH (DRILLER)	2450	2450																																																																																											
TOTAL DEPTH (R/A LOG)	2450	2450																																																																																											
TOP OF LOGGED INTERVAL	100	100																																																																																											
BOTTOM OF LOGGED INTERVAL	2448																																																																																												
FLUID IN HOLE	DRY	DRY																																																																																											
FLUID LEVEL	2447	2444																																																																																											
MAXIMUM RECORDED TEMPERATURE		800N																																																																																											
NEUTRON SOURCE STRENGTH & TYPE		3.75																																																																																											
SOURCE SPACING—IN.		10																																																																																											
LENGTH OF MEASURING DEVICE—IN.	30	2 5/8																																																																																											
O.D. OF INSTRUMENT—IN.	5 0	4 0																																																																																											
TIME CONSTANT—SECONDS	20	20																																																																																											
LOGGING SPEED FT./MIN.	5"	50																																																																																											
	2"	0.7																																																																																											
STATISTICAL VARIATION—IN.	275	0.5																																																																																											
SENSITIVITY REFERENCE		275																																																																																											
RECORDED BY	BARRON	BARRON																																																																																											
WITNESSED BY	ROHME	ROHME																																																																																											
CASING RECORD <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th style="width: 25%;">SIZE—IN.</th> <th style="width: 25%;">WT.—LB.</th> <th style="width: 25%;">WELL RECORD</th> <th style="width: 25%;">BIT SIZE—IN.</th> </tr> <tr> <td>5 1/2</td> <td>14</td> <td>SURFACE TO 2365</td> <td>7 7/8</td> </tr> <tr> <td></td> <td></td> <td>2365 TO 2450</td> <td>4 3/4</td> </tr> <tr><td></td><td></td><td>TO</td><td></td></tr> <tr><td></td><td></td><td>TO</td><td></td></tr> <tr><td></td><td></td><td>TO</td><td></td></tr> </table>		SIZE—IN.	WT.—LB.	WELL RECORD	BIT SIZE—IN.	5 1/2	14	SURFACE TO 2365	7 7/8			2365 TO 2450	4 3/4			TO				TO				TO																																																																					
SIZE—IN.	WT.—LB.	WELL RECORD	BIT SIZE—IN.																																																																																										
5 1/2	14	SURFACE TO 2365	7 7/8																																																																																										
		2365 TO 2450	4 3/4																																																																																										
		TO																																																																																											
		TO																																																																																											
		TO																																																																																											
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th style="width: 50%;">R/A LOG</th> <th style="width: 50%;">TO</th> </tr> <tr><td></td><td>TO</td></tr> <tr><td></td><td>TO</td></tr> <tr><td></td><td>TO</td></tr> <tr><td></td><td>TO</td></tr> </table>		R/A LOG	TO		TO		TO		TO		TO																																																																																		
R/A LOG	TO																																																																																												
	TO																																																																																												
	TO																																																																																												
	TO																																																																																												
	TO																																																																																												
REMARKS OR OTHER DATA																																																																																													

GAMMA RAY		CAS GOL DER	NEUTRON	

→

