

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office **Santa Fe**
Lease No. **078630**
Unit **Foster**
SW/4 Sec. 13 is
Designated Drilling
Unit

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF REDRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

RECEIVED
JUN 25 1956
U.S. GEOLOGICAL SURVEY
FARMINGTON, NEW MEXICO

June 25th, 1956

Well No. 1 is located 1780 ft. from S line and 1190 ft. from W line of sec. 13

NW/4 SW/4 Sec. 13
(1/4 Sec. and Sec. No.)

25N
(Twp.)

8W
(Range)

N.M.P.M.
(Meridian)

Ballard
(Field)

San Juan
(County or Subdivision)

New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is 6975 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Pictured Cliffs Sand test. Estimated total depth 2600'.

Surface Casing: 90' of 8-5/8" OD 24# J-55 cemented to surface.
Production " : Approximately 2500' of 5-1/2" OD 15.5# cemented with 100 sacks.

If commercial production is indicated, the producing section will be shot with nitroglycerin and/or sandfraced.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company PETRO-ATLAS CORPORATION

Address 7th Floor, Simms Building

Albuquerque, New Mexico

By

John G. Colwell

Title President