Farm 9-331 (May 1963)

16.

## UNITED STATES SUBMIT IN TRIPLICATE\* DEPARTMENT OF THE INTERIOR (Other Instructions verse side)

MI 0362.3

	Person apparent	ाती संस्थि	*in	13411121
11 W.	ter storages		11 4	PP137, 50,

GEOLOGICAL SURVEY

	SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  Use "APPLICATION FOR PERMIT—" for such proposals.)	<ul> <li>Эт тубрау, автипу с от тене чама.</li> </ul>	
ì.		7. TINET AGE THEFT TO G	
•	WELL WELL OTHER Water Injection	East Birtl Unit	
2.	NAME OF OFFRATOR	R. PARM OR LEADE MA P	
	Skelly Oil Company		
3.	ADDRESS OF OPERATOR	9. WELL NO.	
	1860 Lincoln Street, Denver, Colorado 80203	3	

LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\* See also space 17 below.)
At surface 10, FIELD AND POOL, OR WILDCAT Bisti Lower Gallup 11. BEC., T., R., M., OR P.R. AND

2056' FSL & 2050' FWL Section 16-25N-11W

Section 16-25N-11W '14, PERMIT NO. 15. ELEVATIONS (Show whether Dr. RT. OR, etc.) 12. COUNTY OR PARINE, 13. STATE New Nextco San Juan

6422.6' GR

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOT	ICB OF	INTENTION TO:	•	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF FRACTURE TREAT		TULL OR ALTER CASING MULTIPLE COMPLETE	VV	WATER SHUT-OFF STRAINING WART, FRACTURE TREATMENT ANALYSIS CARRYS
SHOOT OR ACTOIN		ABANDON®	<u>^  </u>	8HOOTING ON ACIDIZING UNITED AND ACIDIZING
(Other)	لــا	CHANGE PLANS		(Other)  (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log forms

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting an proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) \*

All depths shown are from Ground Level.

This well has reached the economic limit and is no longer profitable to operate. Plans are to plug and abandon this well; plugging as follows:

First Plug - ( 4869'- 4969' ) 100' plug across the Gallup Zone Perfs. 4930-4944'

Second Plug- 50' inside of the 4-1/2'' casing and 50' above where casing is shot in two

Third Plug - ( 1165'- 1315' ) 150' plug extending downward from above the Fruitland coal section across the Pictured Cliffs Sand

Fourth Plug- ( 350'- 450' ) 100' plug extending from 50' above to 50' below the bottom of the Ojo Alamo Sand

10 sacks of cement in top of surface casing with dry hole marker

	<u> </u>					
8. I hereby certify that the forego	ing is true and correct	TITLE	Lead	Clerk	the same of the sa	DATE July 20, 1971
(This space for Federal or Stat	e office use)					
APPROVED BYCONDITIONS OF APPROVAL.		TITLE		3 .		DATE