


(SUBMIT IN TRIPLICATE)

Land Office Santa Fe, New Mexico

Lease No. 5F 070066

Unit _____



UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL _____	SUBSEQUENT REPORT OF WATER SHUT-OFF _____
NOTICE OF INTENTION TO CHANGE PLANS _____	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING _____
NOTICE OF INTENTION TO TEST WATER SHUT-OFF _____	SUBSEQUENT REPORT OF ALTERING CASING _____
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL _____	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR _____
NOTICE OF INTENTION TO SHOOT OR ACIDIZE _____	SUBSEQUENT REPORT OF ABANDONMENT _____
NOTICE OF INTENTION TO PULL OR ALTER CASING _____	SUPPLEMENTARY WELL HISTORY _____
NOTICE OF INTENTION TO ABANDON WELL _____	
<input checked="" type="checkbox"/> Complete well <input checked="" type="checkbox"/>	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

May 24, 1956

Well No. 12-15 is located 1900 ft. from N line and 660 ft. from E line of sec. 15

24 1/4 15 25 N 12 W N.M.P.M.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Blair San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the ~~derish floor above sea level~~ is 6230 ft. (approx. grd.)

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Status: Depth 4900'
Surface casing 8 5/8" cemented at 223'.
Hole sizes: 7 7/8" 223 to 4900'.

Proposed Works

1. Run and cement 5 1/2" casing at 4900' with 200 sacks cement.
2. Clean out to 4885' displace mud with oil.
3. Perforate 4 - 1/2" holes per foot 4810-4792, 4787-4775 and 4766-4756 (10' - 160 holes.)
4. Send oil free with 30,000 gals. oil, 45,000 sand.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations are commenced.


Company SHELL OIL COMPANY

Address 33 RICHARDS STREET

SALT LAKE CITY, UTAH

By B. W. [Signature]

Title Exploitation Engineer



5. Make flowing production test.
6. Set drillable bridge plug at 4752'.
7. Perforate interval 4750-4728 (22' - 88 holes).
8. Sand oil free with 30,000 gals. oil 45,000# sand.
9. Make flowing production test.
10. Set drillable bridge plug at 4721.
11. Set perforate interval 4714-4700 (14' - 56 holes).
12. Sand oil free with 15,000 gals oil, 23,000# sand.
13. Make flowing production test.
14. Clean out bridge plugs.
15. Install Christmas Tree or artificial lift equipment.

