

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Carson

Lease No. SP 078067

Unit Carson

RECEIVED

NOV 19 1959

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

U. S. GEOLOGICAL SURVEY
FARMINGTON, NEW MEXICO

Well No. 42-14 is located 1980 ft. from N line and 660 ft. from E line of sec. 14
25N 12E 100W
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Dist San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)


The elevation of the surface above sea level is 6320 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Spudded 11-9-59

11-9-59 ran and cemented (95') 8-5/8", 24#, J-55 casing at 104 with 100 sacks, to 120 cu. ft. portland cement, treated with 2% calcium chloride, surface temperature 95°F., formation temperature 75°F. Estimated strength after 12 hrs. 1000 psi. Flanged up and waited on cement. Tested B P and casing with 700 psi., OK.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Shell Oil Company

Address Box 158

Farmington, N. Mex.

Original signed by
By B. W. SHEPARD

Title Exploitation Engineer

