

(SUBMIT IN TRIPLICATE)

Indian Agency Navajo

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Allottee **Allotted Lands**

Lease No. 14-20-603-1284

I 18

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	X
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	X
NOTICE OF INTENTION TO ABANDON WELL.....		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

JANUARY 27, 1960

Carbon Unit

Well No. 22-18 is located 1980 ft. from N line and 1980 ft. from W line of sec. 18

NW SE 18

(1/4 Sec. and Sec. No.)

25W

(Twp.)

11W

(Range)

N.M.P.H.

(Meridian)

B1-t1

(Field)

Summary

(County or Subdivision)

New Max100

(State or Territory)

Kelly Bashing

The elevation of the ~~highest point~~ above sea level is 6369 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

U. S. GEOLOGICAL SURVEY
FARMINGTON, NEW MEXICO

1-19-60 Ran and cemented (100') 8-5/8", 28#, J-55 casing at 109' with 100 sacks, 120 cu. ft. Portland cement treated with 2% calcium chloride. Surface temperature 20°F+. Formation temperature 75°F+. Estimated strength of cement after 12 Hours - 1000 psi. Flanged up. Pressure tested casing and BOP with 700 psi, OK.



I understand that this plan of work must receive approval in writing by the Geological Survey before operation may be commenced.

Company Shell Oil Company

Address Post Office Box 158

Farmington, New Mexico

By

M. W. McGarry, Jr.

Title Exploitation Engineer

