

(Orig. 5-2)
ACTING DISTRICT ENGINEER

(SUBMIT IN TRIPLICATE)

Land Office Santa Fe
Lease No. 078630
Unit Foster-Riddle

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	Subsequent Report of Sand-Oil Treatment

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

March 5th, 1956

Well No. 1 is located 1065 ft. from N line and 1850 ft. from E line of sec. 13

NE/4 NW/4 Sec. 13

(1/4 Sec. and Sec. No.)

25N

(Twp.)

8W

(Range)

N.M.P.M.

(Meridian)

Ballard PC

(Field)

San Juan

(County or Subdivision)

New Mexico

(State or Territory)

The elevation of the derrick floor above sea level is 6643 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

2-14-56 TD 2350'. Flowing 2,430 MCF/day. Sand-oil treated from 2298' to 2350' with 6,006 gallons diesel oil and 8,000* sand, flushed with 3,994 gallons diesel oil. Breakdown pressure 1800*, treating pressure 1200*, injection rate 25.1 barrels per minute. After 9 hours flowing 6,800 MCF/day.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company BENSON-MONTIN-GREER DRILLING CORP.

Address 405 1/2 West Broadway

Farmington, New Mexico

By [Signature]

Title Vice-President