

U. S. LAND OFFICE CARTA Fe. N.M.
SERIAL NUMBER M. 036254
LEASE OR PERMIT TO PROSPECT ...

## UNITED STATES DEPARTMENT OF THE INTERIOR

GEOLOGICAL SURVEY

## LOG OF OIL OR GAS WELL

ract Fede 41-16 Sec. 660 ft. $8$ formation given be determined 660 ft. $8$ formation given be determined.	Tompany  Table T25% I  of Line a  ven herewith i  ned from all a  continuous page is for  June 13	R. 127. Nand 700 is a compvailable the cond	$\mathbf{F}$ $\mathbf{M}$ eridian $\mathbf{ft}$ $\mathbf{E}$ $\mathbf{W}$ $\mathbf{V}$ $\mathbf{V}$ of plete and $\mathbf{C}$ records. Signed	ield Li MIM E_ I correct	isti ine of Isc record of th	Sta County Sal Li ne well and	te Beu Juan Eler Coerri	vation 210.7 Place the floor relative to sea level) done thereon	
41-12. Sec. $660$ . ft. $8$ . formation given be determined by $600$ . $12$ mmary on the $600$ sec. $12$	of Line aven herewith it med from all a	R. 127. A and 729. is a compvailable the cond	Meridian  ft. $\left\{ \begin{array}{l} \mathbf{E} \\ \mathbf{W} \end{array} \right\}$ of plete and cords.  Signed	MIM  -Z. I  correct	Line of ISC record of th	County Sel	1 Juan Elev (Derri	vation 260.7 Plack floor relative to sea level) done thereon	
n be determined to be d	ined from all a	is a composable of the cond	plete and c records. Signed	correct	record of th	Skeps	all work	done thereon	
n be determined to be d	ined from all a	is a composable of the cond	plete and c records. Signed	correct	record of th	Skeps	all work	done thereon	
mmary on th	nis page is for	the cond		,		,		•	
mmary on th	nis page is for	the cond	ition of the	1	Title_	TO OTT			
				e well a	it above dat		Mon In	gineer	
		,						, 19 <u>.57</u> _	
			GAS SANI	DS OR			الله ند س. ا	(arrolatur .	
-4759	Grass to	ļģ <i>i</i> ,	(Denote gas N	. ,	rom	<i>.</i>			
	to			To. 5, f	rom		ALLA	INTO/	
	to			,	om	· 1	MOAT	1957	
							M. CAP		
						***	thou.	The state of the s	
		CA	ASING RE	CORD	)				
ht Threads lnch	per Make	Amoun	t Kind of	shoe   C	ut and pulled fr	om From—	rated To-	Purpose	
.,,, 2	Spang								
		1990	Hake	•		4759 Gr	-4859 956	Froduction	
							-		
	BALIFOE	NINC AL	ND CENT		·			# 2 0 0	
ere set									
<del>[}</del>			<del>i dank co</del>	<del>*******</del> ****	·				
y-Material	~======================================	PLUGS	S AND AI Length	DAPTE	RS	Denth set			
laterial			Size						
			OTING R	ECOR	D		· · · · · · · · · · · · · · · · · · ·		
			Quantity	Date	_				
were used fro	om	feet	to <del>2:905</del> -	fee	t, and from		feet to	<u>-</u> feet	
ere used from	J	feet	to	fee	t, and from		feet to	feet	
1	, 19 <i></i> ;;	;		to pro	ducing			19	
luction for the	he first 24 hou	urs was .	<i>212</i> b	arrels	of fluid of v	which 99.9.	% was c	oil;%	
					Gravity,	Bé. 37.	<del>(,1-11</del>		
				ons gas	soline per 1,	000 cu. ft. o	of gas		
		E		ES :	hell oil	Commany a	4.5 ±31.0		
		Limer			· V. Car	(a		, Driller	
· eck	,		ATION R					, Driller	
то-	TO					DEMATION			
1305	4			*	7. 2 2 m. rs				
		-			VALUE				
		,							
	) Sa	Jan 3		Cliff House					
3561	1.5	And the second s		0. isom~Genifea					
3/51	*. · ·	\$44		Toint Mockout					
46-52 	<b>€</b>	<b>\$</b> 277		Tanco <b>r</b>					
			Oall:	luo					
-									
			ļ						
			İ						
	Threads inch  To-  To-  To-  To-  To-  To-  To-  To	MUDD  The to	Threads per to	IMPORTANT WA  to N  CASING RE  to N  CASING RE  that Threads per Inch   Make   Amount   Kind of Inch   Make   Make	IMPORTANT WATER S  to No. 3, fit  No. 4, fit  CASING RECORD  the Threads per Make Amount Kind of shoe C  1 Spang 121 Reker  1990 Huker  MUDDING AND CEMENTING  Bisplacement Method used  Bisplacement Size  PLUGS AND ADAPTE  Material Size  SHOOTING RECORD  Shell used Explosive used Quantity Date  TOOLS USED  were used from feet to fee to fee to fee to feet to	IMPORTANT WATER SANDS  to No. 3, from	IMPORTANT WATER SANDS  No. 3, from	to No. 3, from one to INS  Threads per Make Amount Kind of since Cut and pulled from Perforated Point To Assing Record Point To Assing Record Point To Assing Record Point To To Assing Record Point Point To To To Point Po	

## SHELL OIL COMPANY

Gov't 41-15

Bisti

PD 4A

DRILLING REPORT
FOR PERIOD ENDING

15

(FIELD)

San Juan, New Mexico

6-27-57

(SECTION OF LEASE)
T 25 N, R 12 W

(COUNTY)		Y)		(TOWNSHIP OR RANCHO)					
DAY	DEPTHS		REM/	RKS					
57	FROM	то							
				W of NE Corner Sec 15, T 25 N, R 12 W, County, New Mexico					
			Elevations: DF 6258.8 GR 6249.5 KB 6260.7						
6-19	0	133	Spudded 8:00 AM, 6-19-57. Ran and cemented (121') 8 5/8", 24#, J-55 casing at 133' with 85 sacks construction cement treated with 2% calcium chloride. Good returns to surface. Flanged up and waited on cement. Pressure tested casing and BOP with 700 psi for 15 minutes, OK						
6-21 to 6-25	133	4905	Drilled 4772'.						
6 <del>-</del> 26	4905	TD	Ran Electrical Survey and Microlog.						
6-27			Ran and cemented (4990) 4 1/2", 9.5# casing at 4900 with 150 sactors construction cement treated with 4% gel. Released rig 3:00 PM 6-27-57						
			Checked BOP daily						
			Mud summary Wt 9.4-9.9 #/gal Vis 39-85 sec WL 5-7 cc FC 2/32 in						
				Shell Oil Co Rig #18					
		<del></del>	T BEGINNING OF FERIOD	Drillers: J. Speaker					
	HOLE		ASING SIZE DEPTH SET	E. Babcock					
SIZE	FROM	TO		C. C. Adams					

HOLE CASING SIZE DEPTH SET

DRILL PIPE SIZES