

(SUBMIT IN TRIPLICATE)

Indian Agency Navajo

Allotted

Allottee 14-20-603-1283

Lease No. _____

		X
	18	

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	X
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

February 26

U. S. GEOLOGICAL SURVEY
FARMINGTON, NEW MEXICO
19 60

Carson Unit

Well No. 31-18 is located 660 ft. from N line and 1980 ft. from E line of sec. 18

SE 18

(1/4 Sec. and Sec. No.)

25 N

(Twp.)

11 W

(Range)

18PM

(Meridian)

Bisti

(Field)

San Juan

(County or Subdivision)

New Mexico

(State or Territory)

Kelly Bushing


The elevation of the ~~drill floor~~ above sea level is 6404 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Spudded 1-27-60

1-27-60 Ran and cemented (98%) 8-5/8", 28#, J-55 casing at 107' with 100 sacks,
To 121 cu. ft., Portland cement treated with 2% calcium chloride. Surface
1-28-60 temperature 15° F., formation temperature 75° F. Estimated strength
of cement after 12 hrs., 1000 psi. Pressure tested casing and BOP with
700 psi., OK.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Shell Oil Company

Address P. O. Box 156

Farmington, N.M.

Original signed by
B. W. SHEPARD

By

B. W. Shepard

Title

Exploitation Engineer

