

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.

SUBMIT IN TRIPPLICATE

FORM APPROVED

Budget Bureau No. 1004-0135

Expires: March 31, 1993

5. Lease Designation and Serial No.
14-20-603-326

6. If Indian, Allottee or Tribe Name

7. If Unit or CA. Agreement Designation

Central Bisti Unit

8. Well Name and No.
35

9. API Well No.
30-045-05458

10. Field and Pool, or Exploratory Area
Bisti Lower Gallup

11. County or Parish, State
San Juan, New Mexico

1. Type of Well

☒ Oil Well

☐ Gas Well

☐ Other

2. Name of Operator

Central Resources, Inc.

3. Address and Telephone No.

P.O. Box 1247, Bloomfield, New Mexico 87413 (505)-632-3476

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

660' FSL, 1980' FWL, Sec 9, T25N, R12W

12. CHECK APPROPRIATE BOX(es) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

☐ Notice of Intent

☐ Subsequent Report

☒ Final Abandonment Notice

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Central Resources, Inc. plugged the well in accordance with regulations. Production equipment was removed and the well was plugged.

December 19-21, 2000

- A. Set a CIBP @ 4725' and spot cement on top to 4560' using 75 sacks cement
- B. Set Menefee plug from 1907' to 1807' inside and outside casing using 45 sacks cement
- C. Set Pictured Cliffs plug from 1170' to 1070' inside and outside casing using 30
- D. Place the Fruitland plug from 812' to 712' inside and outside casing using 30 sacks cement
- E. Place surface plug @ 187' across the surface casing shoe @ 137' using 165 sacks cement
- F. Cut well head, install dry marker. Clear and remediate location.

14. I hereby certify that the foregoing is true and correct

Signed Patty Shelton

Title Production Tech.

Date

December 21, 2000

Patty Shelton

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any manner within its jurisdiction.

*See Instruction on Reverse Side