


Form 9-331a
(Feb. 1951)

(SUBMIT IN TRIPLICATE)

Land Office Santa Fe, New Mex.
Lease No. SP 374066
Unit _____

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	<u>Subsequent Report of Well Completion X</u>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

September 20, 1956

Government
Well No. 11-10 is located 660 ft. from N line and 660 ft. from E line of sec. 10
10 (1/4 Sec. and Sec. No.) 25N 12W (Twp.) (Range) (Meridian)
Plati San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

Kellyushing
The elevation of the drill floor above sea level is 6216 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

8-30-56 Ran and cemented 5 1/2", 1lb, J-55 casing at 4912' with 200 sacks
to construction cement. Perforators at 4850', 4810', and 4730'. Flanged
9-3-56 up. Cleaned out to 4887'. Ran Gamma Ray log with collar locator. Ran
perforating gun, perforated (number of shots fired unknown). Lost jet per-
forating gun in hole. Ran washover pipe, washed over to 4837', recovered
30' of strip. Ran in with bit and milled on junk. Circulated and cleaned
out hole.

9-1-56 Rep perforated with four 1/2" jets/foot intervals 4775-4797', 4840-4859',
and 4865-4878'. Ran tubing and set packer at 4713'. Released rig.

9-6-56 Moved in scrubbing unit and made production test as follows:
9-7-56 - flowing, 22.5 hrs., 236 B/D (236 B/D rate), 40/64" bore.

I understand that this plan of work must receive approval in writing from the Geological Survey before operations may be commenced. (over)

Company Shell Oil CompanyAddress 13 Richards StreetSalt Lake City, Utah

B. W. Shepard
B. W. Shepard
Title Exploitation Engineer

DETAILS OF WELL (CONTINUED):

1.15 out, gravity 37.2° API, T.P. 60 psi.

7-8-56 - flowing, 24 hours, 234 bbl. gross, 48/64" beam, 1.43 out, gravity 37.2° API.

7-9-56 - flowing, 22 hours, 210 bbl. gross, (229 B/D rate), 48/64" beam, 0.45 out, gravity 37.2° API.

8-10-56 - flowing, 24 hours, 230 bbl., not out.

Representative Initial Production:

Flowing, 234 B/D gross, 233 B/D clean, out 0.45, 48/64" beam, gravity 37.2° API, T.P. 60.

