


A 10x10 grid with a thick L-shaped axis on the left and bottom. The number '10' is at the intersection of the 5th vertical line and 5th horizontal line. The number 'x' is at the intersection of the 10th vertical line and 1st horizontal line.

LOCATE WELL CORRECTLY



U. S. LAND OFFICE Santa Fe, N.M.
SERIAL NUMBER NM 036254
LEASE OR PERMIT TO PROSPECT -

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

LOG OF OIL OR GAS WELL

Company Shell Oil Company Address 101 S. Behrend, Farmington, N.M.
Lessor or Tract Federal - Gov't. Field Bisti State New Mexico
Well No. 44-10 Sec. 10 T. 25N R. 12W Meridian NMPM County San Juan
Location 790 ft. N. of S. Line and 790 ft. EX of E. Line of Sec. 10 Elevation 6218.9 FB
(Derrick floor relative to sea level)

The information given herewith is a complete and correct record of the well and all work done thereon so far as can be determined from all available records.

Signed _____ Original signed by
B. W. SHEPARD

Date February 11, 1958 Title Exploitation Engineer

The summary on this page is for the condition of the well at above date.

Commenced drilling August 28, 1957 Finished drilling September 3, 1957

OIL OR GAS SANDS OR ZONES

(gross)

(Denote gas by G)

No. 1, from 4747 to 4845 No. 4, from _____ to _____

No. 2, from _____ to _____ No. 5, from _____ to _____

No. 3, from _____ to _____ No. 6, from _____ to _____

IMPORTANT WATER SANDS

No. 1, from _____ to _____ No. 3, from _____ to _____

No. 2, from _____ to _____ No. 4, from _____ to _____

CASING RECORD

Size casing	Weight per foot	Threads per inch	Make	Amount	Kind of shoe	Cut and pulled from	Perforated		Purpose
							From—	To—	
8-5/8"	24	8	-	79	Baker	-	-	-	Surface
4-1/2"	9.5	8	-	4877	Baker	-	4747	4845	Production
							(gross)		

MUDDING AND CEMENTING RECORD

Size casing	Where set	Number sacks of cement	Method used	Mud gravity	Amount of mud used
8-5/8"	89	85	Displacement	-	-
4-1/2"	4887	150	"	-	-

PLUGS AND ADAPTERS

Heaving plug—Material _____ Length _____ Depth set _____

Adapters—Material _____ Size _____

SHOOTING RECORD

[illegible]

TOOLS USED

Rotary tools were used from 0 feet to 1800 feet, and from 0 feet to 0 feet

Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet.

DATES

February 11, 1958 Put to producing January 31, 1958

The production for the first 24 hours was 704 barrels of fluid of which 99.9% was oil; -----% emulsion; -----% water; and 0.1% sediment. Gravity, API. Approx. 39° API-----

If gas well, cu. ft. per 24 hours _____ Gallons gasoline per 1,000 cu. ft. of gas _____

Rock pressure, lbs. per sq. in. -----

EMPLOYEES

-----, Driller

R. C. Cary, Driller

FORMATION RECORD

FROM—	TO—	TOTAL FEET	FORMATION
1067	1280	213	Pictured Cliffs
1280	1455	175	Lewis
1455	1930	475	Cliff House
1930	3573	1643	Allison - Menefee
3573	4470	897	Point Lookout
4470	4646	176	Mancos
4646	-	-	Gallup

