

Form 3160-5  
(June 1990)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT  
SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or completion of wells in different reservoirs.  
Use APPLICATION FOR PERMIT for such proposals.

SUBMIT IN TRIPLICATE

FORM APPROVED

Budget Bureau No. 1004-0135

Expires: March 31, 1993

5. Lease Designation and Serial No.  
14-20-603-326

6. If Indian, Allottee or Tribe Name

7. If Unit or CA. Agreement Designation

Central Bisti Unit

8. Well Name and No.  
27

9. API Well No.  
30-045-05471

10. Field and Pool, or Exploratory Area  
Bisti Lower Gallup

11. County or Parish, State  
San Juan, New Mexico

1. Type of Well  
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator  
Central Resources, Inc.

3. Address and Telephone No.  
P.O. Box 1247, Bloomfield, New Mexico 87413 (505) 832-3475

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)  
☒ 1980' FSL, 1980' FWL, Sec 9, T25N, R12W

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA  
TYPE OF SUBMISSION

☐ Notice of Intent  
☐ Subsequent Report  
☒ Final Abandonment Notice

☒ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☐ Other

☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*  
Central Resources, Inc. plugged the well in accordance with regulations. Production equipment was removed and the well was plugged.

December 20-26, 2000

- A. Cover top of Gallup plug to 4586" using 20 sacks cement.
- B. Cover top of Mesa Verde plug from 1811' to 1911' inside and outside the 4 1/2" casing using 51 sacks cement.
- C. Set Pictured Cliffs plug from 1175' to 1075' inside and outside the 4 1/2" casing using 51 sacks cement.
- D. Place the Fruitland plug from 844' to 744' inside and outside the 4 1/2" casing using 51 sacks cement.
- E. Place the surface plug inside and outside the 4 1/2" casing from 365' to surface to cover the Ojo Alamo interval with 135 sacks.

14. I hereby certify that the foregoing is true and correct

Signed Patty Shelton Title Production Tech. Date January 22, 2001

(This space for Federal or State office use)

Approved by \_\_\_\_\_ Title \_\_\_\_\_ Date \_\_\_\_\_

Conditions of approval, if any:

ACCEPTED FOR RECORD

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any manner within its jurisdiction.

\*See Instruction on Reverse Side

IV 5000 OFFICE