

Cemented

FORM APPROVED

Budget Bureau No. 1004-0135

Expires: March 31, 1993

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
SUNDRY NOTICES AND REPORTS ON AND FOR

Do not use this form for proposals to drill, complete, or alter wells. Use APPLICATION FOR PERMIT TO DRILL FOR PROPOSAL.

SUBMIT IN TRIPlicate

5. Lease Designation and Serial No.

NM/070322A

6. If Indian, Allottee or Tribe Name

7. If Unit or CA. Agreement Designation

Central Bisti Unit

1. Type of Well

☒ Oil Well

☐ Gas Well

☐ Other

2. Name of Operator

Central Resources, Inc.

3. Address and Telephone No.

P.O. Box 1247, Bloomfield, New Mexico 87413 (505)-632-3476

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FSL, 700' FWL, Sec 10, T25N, R12W

8. Well Name and No.

25 Central Bisti Unit

9. API Well No.

30-045-05473

10. Field and Pool, or Exploratory Area

Bisti Lower Gallup

11. County or Parish, State

San Juan, New Mexico

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

☐ Notice of Intent

☐ Subsequent Report

☒ Final Abandonment Notice

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Central Resources, Inc. plugged the well in accordance with regulations. Production equipment was removed and the well was plugged.

December 6-8th, 2000

A. Bring top of Gallup plug to 4499' to cover top @ 4549' using 20 sacks cement.

B. Set Mesa Verde plug from 1868' to 1768' inside and outside casing using 51 sacks cement.

C. Set Pictured Cliffs plug from 1125' to 1025' inside and outside casing using 51 sacks cement.

D. Place the Fruitland plug from 767' to 667' inside and outside casing using 51 sacks cement.

E. Place surface plug @ 153' inside and outside casing across the surface casing shoe @ 103' using 65 sacks cement.

14. I hereby certify that the foregoing is true and correct

Signed

Patty Shelton

Title Production Tech.

Date

December 7, 2000

Patty Shelton

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

ACCEPTED FOR RECORD

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any manner within its jurisdiction.

*See Instruction on Reverse Side

FR 0-2001

SMW