

Form 3160-5  
(June 1990)

FORM APPROVED

Budget Bureau No. 1004-0135

Expires: March 31, 1993

5. Lease Designation and Serial No.  
SF 078056

6. If Indian, Allottee or Tribe Name

7. If Unit or CA. Agreement Designation

Central Bisti Unit

8. Well Name and No.  
33

9. API Well No.  
30-045-05474

10. Field and Pool, or Exploratory Area  
Bisti Lower Gallup

11. County or Parish, State  
San Juan, New Mexico

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Central Resources, Inc.

3. Address and Telephone No.

P.O. Box 1213, Bloomfield, New Mexico 87413 (505)-632-3476

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FSL, 660' FEL, Sec 7, T25N, R12W

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

☐ Notice of Intent

☐ Subsequent Report

☒ Final Abandonment Notice

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Central Resources, Inc. plugged the well in accordance with regulations. Production equipment was removed and the well was plugged starting December 28 and ending December 30, 2000.

- A. Set cement retainer @ 4800'. Pump 31 sacks Class "H" cement into Lower Gallup to 4630'
- B. Cover top of the Mesa Verde from 1990' to 1890' using 51 sacks cement inside and outside casing.
- C. Cover top of the Pictured Cliffs from 1215' to 1115' using 53 sacks cement, inside and outside casing
- D. Cover top of the Fruitland Coal from 914' to 814' using 51 sacks cement, inside and outside casing,
- E. Circulate 121 sacks of cement from 520' to surface leaving both inside and outside of casing full of cement.
- F. Place the 3 1/2" casing shoe plug 4294'-3939' both inside and outside of casing using 20 sacks cement.

14. I, Patty Shelton

Title Production Tech.

Date

December 21, 2000

Si (This space for Federal or State office use)

Title

Date

Conditions of approval, if any:

Approved by

ACCEPTED FOR RECORD

Title 18 U.S.C. Section 1001, makes it a crime for a fictitious or fraudulent statements or representations as to any manner within its jurisdiction. \*See Instruction on Reverse Side

CR 0 2001

OFFICE