Bisti

BRILL PIPE

(FIELD) San Juan, New Mexico (county)

DRILLING REPORT FOR PERIOD ENDING

November 23, 1959

11 (SECTION OR LEASE) T. 25 N., R. 12 W. (TOWNSHIP OR RANCHO)

DAY	DEI	PTHS	REMARKS	
]	FROM	то		
			Location: 1980' N. and 1977' E. of SW Corner, Section 11, T. 25 R. 12 W., N.M.P.M., San Juan County, New Mexico Elevations: DF 6263.8' GR 6256.3' KB 6265.3'	N.,
11-16 to 11-17	0	1630	Spudded 6:45 P.M., 11-16-59. Ran and cemented 1) 3-5/8", 28#, casing at 106' with 100 sacks cement treated vi	ride.
11-18 to 11-22	1630	4940	Drilled 3310'	
11-23	4940 (TD)		Ran Micro-SP Log. Ran and cemented (4929°) 4-100, 9.5#, J-55 ca at 4938° with 150 sacks cement treated with 45000. Displaced with oil. Final pressure 1800 psi. Released rights P.M., 11-23-59. Checked BOP daily Mud Summary Wt 9.4 - 9.8 #/g vis 46 - 120 sec W1 6 - 7 cc FC 1-2/32° Contractors Brinkerhoff Drilling Compand Drillers: J. Speaker E. Babcock W. Black	.th
		ONDITIO	AT BEGINNING OF PERIOD	
	HOLE		ASING SIZE DEPTH SET	
SIZE	FROM	70		

SHELL OIL COMPANY

Carson Unit 23-11

Bisti

DRILLING REPORT FOR PERIOD ENDING

11
(SECTION OR LEASE)
T. 25 N., R. 12 W.

Cara Tra	(FIELD)	W	TOR PERIOD ENDING	(SECTION OR LEASE)
San Jua	(COUNTY)	w Mexi	co December 9, 1959	T. 25 N., R. 12 W. (TOWNSHIP OR RANCHO)
I				
DAY	DEPTH	ıs		
PT	ROM	то	REMARKS	
1 '1 ''	940 TD		Perforated four 1/2" holes/ft. 4300-4819, 4825-4830	, 4872-4884, and
11-25			Spotted 200 gal. and acid. Sand call fractured with 1.66#/gal. sand. Maximum pressure 2400 psi, droppe with pressure increases of 50-100 psi after each la	d 150 rubber balls
11-26 to 11-27			Cleaned out frac sand from 4870' to 4930'. Ran 2-3 rods and pump.	/8" tubing to 4820°,
11-28 to 12-9			Pumped and recovered all load and francil, 1974 bb INITIAL PRODUCTION Pumping, 208 B/D grass, 208 B/D slean, rat 0 GOR 1495. Completed 12-10-59.	

	HOLE		CABING SIZE	DEPTH SET
SIZE	FROM	то		
! -1/ 4"	0	115	8-5/8*	106°
-7/8 #	115	149110	4-1/2"	149 38°
		<u> </u>		

SIGNED