

FORM APPROVED

Budget Bureau No. 1004-0135

Expires: March 31, 1993

5. Lease Designation and Serial No.
14-20-603-1228

6. If Indian, Allottee or Tribe Name

7. If Unit or CA. Agreement Designation

Central Bisti Unit

8. Well Name and No.
26

9. API Well No.
30-045-05480

10. Field and Pool, or Exploratory Area
Bisti Lower Gallup

11. County or Parish, State
San Juan, New Mexico

1. Type of Well
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator
Central Resources, Inc.

3. Address and Telephone No.
P.O. Box 1247, Bloomfield, New Mexico 87413 (505)-632-3476

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
1980' FSL, 660' FEL, Sec 9, T25N, R12W 1

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA
TYPE OF SUBMISSION

☐ Notice of Intent
☐ Subsequent Report
☒ Final Abandonment Notice

TYPE OF ACTION

☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*
Central Resources, Inc. plugged the well in accordance with regulations. Production equipment was removed and the well was plugged.

January 15-17, 2001

- A. Cover top of Gallup plug to 4501' using 20 sacks cement.
- B. Cover top of Mesa Verde plug from 1739' to 1839' inside and outside the 4 1/2" casing using 50 sacks cement
- C. Set Pictured Cliffs plug from 1096' to 996' inside and outside the 4 1/2" casing using 50 sacks cement.
- D. Place the Fruitland plug from 738' to 638' inside and outside the 4 1/2" casing using 50 sacks cement.
- E. Place the surface plug from 276' to 376' across the surface casing shoe at 326' inside and outside the 4 1/2" casing using 50 sacks cement.
- F. Place the surface plug inside and outside the 4 1/2" casing from 70' to surface to cover the Ojo Alamo interval with 130 sacks.

14. I hereby certify that the foregoing is true and correct

Signed Patty Shelton Title Production Tech. Date January 22, 2001

(This space for Federal or State office use)

Approved by _____ Title _____ Date _____

Conditions of approval, if any:

ACCEPTED FOR RECORD

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any manner within its jurisdiction.

*See Instruction on Reverse Side

FR 0 2001

ADMIN 3Y SM OFFICE