

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe, N.M.

Lease No. SP 078067

Unit Carson Unit

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

October 21, 1958

Carson Unit

Well No. 22-11 is located 1980 ft. from N line and 1980 ft. from E line of sec. 11

NW 11

25N

12W

10TH

($\frac{1}{4}$ Sec. and Sec. No.)

(Twp.)

(Range)

(Meridian)

Bisti

San Juan

New Mexico

(Field)

(County or Subdivision)

(State or Territory)

Kelly Bunning


The elevation of the derrick floor above sea level is 6361 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Spudded 10-13-58

10-13-58 Ran and cemented (97') 6-5/8", 24#, J-55 casing at 107' with 100 sacks cement to treated with 2% calcium chloride (122 cu. ft. Portland cement, 75° surface temperature, 68° (approx) formation temperature, estimated strength 950 psi, cement in place 12 hrs. prior to test). Flanged up. Pressure tested casing and POP with 500 psi, OK.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Shell Oil Company

Company

705 W. Municipal Drive

Address

Farmington, New Mexico

By

B. W. Shepard

Title

Exploitation Engineer