

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

**SUBMIT IN TRIPLICATE**

1. Type of Well  
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Giant Exploration & Production Company

3. Address and Telephone No.

P.O. Box 2810, Farmington, N.M. 87499

(505) 326-3325

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1880' FNL, 1980' FWL, Sec. 10, T25N, R12W

5. Lease Designation and Serial No.  
14-20-603-1449

6. If Indian, Allottee or Tribe Name

Navajo Allotted

7. If Unit or CA, Agreement Designation

Central Bisti Unit

8. Well Name and No.

CBU Well No. 24

9. API Well No.

30-045-05498

10. Field and Pool, or Exploratory Area

Bisti Lower Gallup

11. County or Parish, State

San Juan, New Mexico

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SURFACING

☐ Notice of Intent

☐ Subsequent Report

☒ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

On December 30, 1992 Giant Exploration & Production Company plugged and abandoned the subject well as follows:

1. Spotted cement across Gallup perforations (4802' - 4903') with 109 sks Class "B" cement. Plug is from 3866' to 4832'.
2. Filled casing from 3791' to 691' with 75 bbls 8.4# and 41 vis mud.
3. Shot 4 squeeze holes at 1542'. Set cement retainer at 1458'.
4. Spotted cement across tops of ~~Mesa Verde~~ <sup>Chaco</sup>, Picture Cliffs and Fruitland formations with 289 sks Class "B" cement. Displaced 199 sks below the retainer and spotted 90 sks on top of the retainer. Cement top at 664'.
5. Shot 2 squeeze holes at 380'. Mixed and pumped 150 sks Class "B" cement down casing and broke circulation out bradenhead. Circulated cement to surface.
6. Cut off wellhead and installed regulation dry hole marker.

14. I hereby certify that the foregoing is true and correct

Signed John C. Corbett Title Vice President  
(This space for Federal or State office use)

Approved by \_\_\_\_\_  
Conditions of approval, if any:

Title MANAGER

Date JAN 23 1993

AREA MANAGER