

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT--" for such proposals

SUBMIT IN TRIPLICATE

FORM APPROVED

Budget Bureau No. 1004-0135

Expires: March 31, 1993

5. Lease Designation and Serial No.
SF 078056

6. If Indian, Allottee or Tribe Name

7. If Unit or CA. Agreement Designation

Central Bisti Unit

1. Type of Well
☐ Oil Well ☐ Gas Well ☒ Other Water Injection Well

8. Well Name and No.
Central Bisti Unit-19

2. Name of Operator
Central Resources, Inc. for Giant Exploration & Production Company

9. API Well No.
30-045-055014

3. Address and Telephone No.
P.O. Box 1213, Bloomfield, New Mexico 87413 (505)632-3476

10. Field and Pool, or Exploratory Area
Bisti Lower Gallup

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
660' FNL, 660' FEL, Sec. 7, T25N, R12W

11. County or Parish, State
San Juan, New Mexico

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

☐ Notice of Intent

☐ Subsequent Report

☒ Final Abandonment Notice

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

January 2-5th.

- A. Set a CIBP at 4758' and spot cement on top to 4658' using 30 sacks cement.
- B. Bring top of Gallup plug from 4588' to 4420' inside outside 5 1/2" casing using 30 sacks cement.
- C. Set Mesa Verde plug from 1962' to 1926' inside and outside 5 1/2" casing using 47 sacks cement.
- D. Set the Pictured Cliffs Plug from 1230' to 1184' inside and outside 5 1/2" casing using 47 sacks cement.
- E. Set the Fruitland Coal plug from 910' to 873' inside and outside 5 1/2" casing using 47 sacks cement.
- F. Place the surface plug at 242' to surface inside and outside the 5 1/2" casing using 95 sacks cement
- H. Cut well head and install dry hole marker. Clear and remediate location.

14. I hereby certify that the foregoing is true and correct

Signed Patty Shelton Title Production Technician Date 01/15/2001

(This space for Federal or State office use)

Approved by _____ Title _____ Date _____
Conditions of approval, if any:

FOR RECORD

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any manner within its jurisdiction.

AN 19 2001

*See Instruction on Reverse Side

ADMINISTRATIVE OFFICE