

Q member

Form 3160-5  
(June 1993)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or cement or otherwise alter or modify.  
Use APPLICATION FOR PERMIT for such proposals.

SUBMIT IN TRIPLICATE

FORM APPROVED

Budget Bureau No. 1004-0135

Expires: March 31, 1993

5. Lease Designation and Serial No.  
NM 036254A

6. If Indian, Allottee or Tribe Name

7. If Unit or CA. Agreement Designation

1. Type of Well

☒ Oil Well

☐ Gas Well

☐ Other

2. Name of Operator

Central Resources, Inc.

3. Address and Telephone No.

P.O. Box 1247, Bloomfield, New Mexico 87413 (505)-632-3476

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

660' FNL, 660' FEL, Sec 9, T25N, R12W

Central Bisti Unit

8. Well Name and No.

13 Central Bisti Unit

9. API Well No.

,30-045-05518

10. Field and Pool, or Exploratory Area

Bisti Lower Gallup

11. County or Parish, State

San Juan, New Mexico

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

☐ Notice of Intent

☐ Subsequent Report

☒ Final Abandonment Notice

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Central Resources, Inc. plugged the well in accordance with regulations. Production equipment was removed and the well was plugged.

December 8-11, 2000.

A. Set a CIBP @ 4725' and spot cement on top to 4560' using 80 sacks cement.

B. Set Menefee plug from 1907' to 1807' inside and outside casing using 51 sacks cement

C. Set Pictured Cliffs plug from 1170' to 1070' inside and outside casing using 51 sacks cement

D. Place the Fruitland plug from 812' to 712' inside and outside casing using 51 sacks cement

E. Place surface plug @ 187' inside and outside across the surface casing shoe @ 137' using 165 sacks cement

F. Cut well head, install dry marker. Clear and remediate location.

14. I hereby certify that the foregoing is true and correct

Signed Patty Shelton Title Production Tech. Date December 21, 2000

(This space for Federal or State office use)

Approved by \_\_\_\_\_ Title \_\_\_\_\_ Date \_\_\_\_\_

Conditions of approval, if any:

ACCEPTED FOR RECORD

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any manner within its jurisdiction.

NOV 2001

\*See Instruction on Reverse Side

WUCB

SMC OFFICE